

### India Meteorological Department Mausam Bhawan, Lodi Road New Delhi-110003

## **NOTICE INVITING TENDER (NIT)**

## Tender Enquiry No. CPU/53/1021/1546

Dated: 30.11.2021

- 1. Director General of Meteorology (DGM), India Meteorological Department (IMD), Ministry of Earth Sciences (MoES), Government of India, on behalf of President of India invites, ONLINE tenders in two bid system i.e. (i) Technical bid & (ii) Price bid (Separately) from eligible and qualified **Indian Bidders** for procurement of following Goods/Articles/Services.
- 2. Name of Goods/Articles/Services :

Procurement of 8 (Eight) Nos. of X-Band Dual Polarized Doppler Weather Radars (with SSPA Transmitter).

3. Specification and Quantity:

1.	PRE BID Conference	15.12.2021 / 1100 Hrs.
		Place – Mausam Bhawan,
		Lodi Road, New Delhi-110003
		Tele : 011 - 43824224
2.	Closing date and time for submission of	14.01.2022 / 1700 Hrs.
	tender	
3.	Tender Opening date & time	18.01.2022/ 1200 Hrs.
	(Technical Bid)	
4.	Place of Tender Opening	Central Purchase Unit,
		O/o DGM, IMD,
		Lodi Road ,New Delhi.

As per "RFP"

4. Tender schedule is as follows:

- 5. Earnest Money Deposit (EMD): As per Office Memoandum No.F.9/4/2020-PPD dated 12.11.2020 issued by Ministry of Finance Department of Expenditure PPD, No EMD is required for the tender. The firm has to submit a signed Bid Security Declaration as per Annexure-III on their company letter head failing which their bid will be declared as unresponsive.
- 6. All prospective bidders are requested to attend the **Pre-bid meeting** as per venue, date and time indicated in the Para 4 above. Maximum two representatives of a firm with proof of their COVID-19 Vaccination Certificate of 2<sup>nd</sup> Dose, will be allowed to participate in Pre-Bid meeting. The prospective bidders are requested to send their queries preferably 5 days in advance before scheduled pre-bid meeting, on email: radarlab@gmail.com.

- 7. Bidders may download the **Tender Enquiry Document** from the web site <u>www.imd.gov.in</u> & <u>www.eprocurement.gov.in/cpp</u> and read the tender documents carefully before uploading the tender on CPP Portal.
- 8. The following 2 clauses may also be read under "Eligibility Criteria" of the Tender document :-
  - Bidder has to submit a compliance certificate that comply with the Govt Order No. P-45021/2/2017-B.E.-II, Ministry of Commerce and Industry, Department of Industrial Policy and Promotion of Industry and Internal Trade (PP Section) dated 16.09.2020 and instructions issued from time to time failing which their bid shall not be accepted and liable to be rejected.
  - (ii) Compliance of Rule 14(xi) of the GFR 2017 which mandates the bidder from a country sharing land border with India to be registered with the competent authority. Bidder has to submit a compliance certificate that they comply with the Govt Order F.No. 6/18/2019-PPD dated 23<sup>rd</sup> July, 2020 of Ministry of Finance, DoE, Public Procurement Division, failing which their bid shall not be accepted and liable to be rejected.
- 9. Bidders shall ensure that their tenders are complete in all respects before uploading the same on CPP Portal. CPU will not be held responsible for any delay or corruption in the uploaded bids.
- 10. In the event of the tender opening date being declared as holiday for the purchase organization, the tender will be opened on the next working day. The venue and time of tender opening will remain the same.
- 11. Purchaser: The President of India Through Director General of Meteorology, India Meteorological Department, Lodi Road, New Delhi-110003 12. Consignee: DGM (UAID), India Meteorological Department, Lodi Road, New Delhi-110003 13. **Inspecting Authority:** Director General of Meteorology, India Meteorological Department, Lodi Road, New Delhi-110003. 14. Inspection officer : Authorized Representative of Inspecting Authority Director, Central Purchase Unit (CPU) O/o Director General of Meteorology, India Meteorological Department, Lodi Road, New Delhi-110003. Page 2 of 5



भारत मौसम विज्ञान विभाग लोदी रोड, नई दिल्ली -110003

निविदा आमंत्रित करने की सूचना (एन आई टी)

# निविदा जाँच सं. CPU/53/1021/1546

**दिनांक: 30** नवम्बर 2021

- मौसम विज्ञान के महानिदेशक (मौविमनि) भारत मौसम विज्ञान विभाग (भा.मौ.वि.वि.) पृथ्वी विज्ञान मंत्रालय, भारत सरकार, भारत के राष्ट्रपति की ओर से नीचे लिखे सामान / वस्तुएँ / सेवाओं की आपूर्ति, संस्थापन और आरंभ के लिए भारतीय पात्र और अर्हक निविदाकारों से दो बिड प्रणाली अर्थात (एक) तकनीकी बिड और (दो) दर बिड में ओनलाइन टेंडर आमंत्रित करते हैं.
- 2. सामान/ वस्तुएँ/ सेवाओं का नामः Procurement of 8 (Eight) Nos. of X-Band Dual Polarized Doppler Weather Radars (with SSPA Transmitter).
- 3. विनिर्देशन और मात्रा : विनिर्देशन आर एफ पी के अन्सार, (मात्रा-01)
- 4. निविदा अनुसूची इस प्रकार हैः

1	प्री बिड कांफ्रेंस	दिनांक	15.12.2021 / 1100 बजे	
2.	निविदा जमा करने की अंतिम तिथि व समय	दिनांक	14.01.2022 / 1700बजे	
3.	निविदा खोलने की तिथि व समय (तकनीकी बिड)	दिनांक	18.01.2022 / 1200बजे	
4.	निविदा खोलने का स्थान	केंद्रीय क्रय एकक, मौविमनि का कार्यालय		
		भा.मौ.वि.वि , लोदी रोड, नई दिल्ली		

 धरोहर राशि (ई एम डी): वित् मंत्रालय, व्यय विभाग पीपीडी के कार्यालय ज्ञापन स. ऍफ़.९/४/२०२०-पीपीडी दिनांक १२/११/२०२० के अनुपालन में फर्मो को धरोहर राशी (ई ऍम डी) जमा करना आवश्यक नहीं है
 फर्मों को अपनी कंपनी के लैटर हेड पर निविदा दस्तावेज़ के अनुबंध-III के अनुसार एक हस्ताक्षरित बोली सुरक्षा घोषणा प्रस्तुत करनी होगी, ऐसा न करने पर उनकी बोली को अनुत्तरदायी घोषित कर दिया जायेगा । 6. सभी संभावित बोलीदाताओं से अनुरोध है कि वे उपरोक्त पैरा 4 में उल्लिखित स्थल, तिथि और समय अनुसार **बोली पूर्व बैठक में भाग लें** । एक फर्म के अधिकतम दो प्रतिनिधियों को उनके द्वितीय खुराक के कोविद-१९ टीकाकरण प्रमाण पत्र के प्रमाण के साथ बोली पूर्वक बैठक में भाग लेने की अनुमति दी जाएगी | संभावित बोलीदाता अपने प्रश्नों को अधिमानित 5 दिन पहले निर्धारित प्री-बिड मीटिंग से पहले ईमेल : radarlab@gmail.com पर भेजे ।

7. बोलीदाता वेब साइट www.imd.gov.in और www.eprocurement.gov.in से निविदा पूछताछ दस्तावेज डाउनलोड कर सकते हैं और सीपीपी पोर्टल पर निविदा अपलोड करने से पहले निविदा दस्तावेजों को ध्यान से पढ़ सकते हैं। निविदाकर्ताओं को यह सुनिश्चित करना होगा कि उनकी सभी निविदाएँ सभी तरह से पूर्ण हैं किसी भी प्रकार के विलम्ब अथवा नुकसान के लिए क्रय संगठन जिम्मेवार नहीं होगा।

8. निविदा दस्तावेज के "पात्रता मानदंड" के तहत निम्नलिखित 2 खंड भी पढ़े जा सकते हैं: -(i) बोलीदाता को एक अनुपालन प्रमाण पत्र प्रस्तुत करना होगा जो सरकार के आदेश संख्या पी-45021/2/2017-बीई-द्वितीय, वाणिज्य और उद्योग मंत्रालय, औद्योगिक नीति और उद्योग और आंतरिक व्यापार संवर्धन विभाग (पीपी अनुभाग) का अनुपालन करता है। ) दिनांक 16.09.2020 और समय-समय पर जारी निर्देश, जिसमें विफल रहने पर उनकी बोली स्वीकार नहीं की जाएगी और अस्वीकार कर दी जाएगी।

(ii) जीएफआर 2017 के नियम 14(xi) का अनुपालन जो भारत के साथ भूमि सीमा साझा करने वाले देश के बोलीदाता को सक्षम प्राधिकारी के साथ पंजीकृत होने के लिए अनिवार्य करता है। बोलीदाता को एक अनुपालन प्रमाण पत्र प्रस्तुत करना होगा कि वे सरकार के आदेश एफ.सं. का अनुपालन करते हैं। 6/18/2019-पीपीडी दिनांक 23 जुलाई, 2020 वित्त मंत्रालय, डीओई, सार्वजनिक खरीद विभाग, में विफल होने पर उनकी बोली को स्वीकार नहीं किया जाएगा और अस्वीकार कर दिया जाएगा।

- यदि निविदा खोलने की तारीख के दिन क्रय संगठन का अवकाश घोषित होता है तो निविदा अगले कार्य दिवस को खोली जाएगी ।निविदा खोलने का स्थान और तारीख वही रहेंगे ।
- यदि निविदा खोलने की तारीख के दिन क्रय संगठन का अवकाश घोषित होता है तो निविदा अगले कार्य दिवस को खोली जाएगी। निविदा खोलने का स्थान और तारीख वही रहेंगे।
- 11.
   क्रयकर्ताः
   भारत के महामहिम राष्ट्रपति

   भा.मौ.वि.वि. के माध्यम से
   भारत मौसम विज्ञान विभाग,

   लोदी रोड, नई दिल्ली-110003
- 12.
   परेषितिः
   मौसम विज्ञान के महानिदेशक (यू ए आई डी)

   भारत मौसम विज्ञान विभाग
   भारत मौसम विज्ञान विभाग

   लोदी रोड, नई दिल्ली-110003
   Page 4 of 5

13.	जाँच प्राधिकारीः	मौसम विज्ञान के महानिदेशक
		भारत मौसम विज्ञान विभाग
		लोदी रोड, नई दिल्ली-110003
14.	जाँच अधिकारीः	जाँच प्राधिकारी का प्राधिकृत प्रतिनिधि
		निदेशक, केंद्रीय क्रय एकक (कें.क्र.ए) ,
		मौसम विज्ञान के महानिदेशक का कार्यालय,
		लोदी रोड, नई दिल्ली- 110003
		टेलीफैक्स सं. : 011-24698148

17564/2021/UAID DGMHQ





Government of India Ministry of Earth Sciences India Meteorological Department Lodi Road New Delhi-110003

> TENDER DOCUMENT No.

> > FOR

# PROCUREMENT OF

# DOPPLER WEATHER RADAR SYSTEMS X-BAND DUAL POLARIZATION FOR NORTH-EAST

(WITH SSPA TRANSMITTER)

÷

July, 2021 Upper Air Instruments Division

## 102/203

# INDEX

CHAPTER	DESCRIPTION	PAGE NO.
1	Instructions to Bidders (ITB)	4
2	Conditions of contract (CoC)	13
3	Schedule of requirements, specifications & allied technical details	31
4	Price schedule	54
5	Annexures (Other standard forms)	56



# CONTENTS

S.No	Descri	iption	Page No.
1	Instructions to bidders		4
2	Conditi	ons of contract	13
3	Schedule of requirements, specifications & allied technical details		難
4	Frice s	chedule (financial bid format)	54
5	Other s	tanderd forms	
é.	361 - 3	Annexute - I Checklist	56
	(41)	Annexure - II Tender terms and conditions acceptance form	58
	34113)	Annemure - III Model bank guarantee format for fornishing EMD	60
	(4v)	Annexare - IV Bank quarantes model format for performance security	61
	ANS .	Annexuse -V Terms and conditions of CAMC	63
	(v1)	Annexure - VI Format for deliverables for supply of 08 nos. 35PA based M-Band dual polarized Doppler weather Radars)	65
	(v11)	Annexure - VII Proforma for performance statement	68
	(111)	Annexure - VIII List of locations for installation of radar	69
	(2.8)	Annexure - IX Fre-contract integrity pact	70
	fx.)	Annemure - X Proforms for certificate from the user indicating successful operation of radar	77
	(xž)	Annerure- XI Nob-Blacklisting Seclaration	7.8
	(RII)	Annexure- XII Compliance table for technical evaluation	79
	(3111)	Annexure-XIII Form of Affidavit for Self Certification regarding Local Content in Doppler Weather Reder	102



## CHAPTER-1

#### INSTRUCTIONS TO BIDDERS

## 1. Introduction:

The India Meteorological Department (IMD) has issued this Tender Enquiry document for purchase of goods/stores/articles and related services as mentioned in "Request for Proposal (TENDER DOCUMENT)" which also indicates, inter alia, the required stores, delivery schedule, terms and conditions and place of delivery atc.

This section ("Instructions to Bidders") provides the relevant information as well as instructions to assist the prospective bidders in preparation and submission of tenders.

Bidders shall have accept all the terms and conditions of tender including payment terms etc.

Anceptance shall be unconditional and bidders shall have no claim and right in future on their terms, if any.

#### 2. Language of Tender:

The tender submitted by the bidder and all subsequent correspondence and documents relating to the tender exchanged between the bidder and IMD, shall be written in English language.

#### 3. Eligibility:

a) Bid is open to all Indian GEMs of weather radars. The bids are only open for Class I local supplier and class II local suppliers. Purchase preference would be available for Class I local supplier. As per Govt. of India Procurement Policies;

"Class-I bonal supplier" means a supplier or service provider, whose goods of service offered for procurement, has local content equal to or more than 50% as defines as prescribed in DIPP Order No.P-45021/2/2017-PP (BE-II) dated 4<sup>th</sup> June, 2020 or by the competent Ministries/Departments in pursuance of this order.

"Class-II Local supplier" means a supplier or service provider, whose goods or service offered for producement, has local content more than 20% but less than 50% as defined as prescribed in DIFP Order No.P-43021/2/2017-PP (RE-II) dated 4<sup>th</sup> June, 2020 or by the competent Ministries/Departments in pursuance of this order.

"Local content" means the amount of value added in India which shall, unless otherwise prescribed by Nodal Ministry,

be the total value of the items produced (excluding net demestic indirect taxes) minus the value of imported content in the item (including all dustom duties) as a proportion of the total value, in percent.

- b) The prime bidder, hereinafter referred simply as the 'The bidder'. Bidders should not be associated, or have been associated in the past, directly or indirectly, with a firm or any of its affiliates which have been engaged by IMD to provide consulting services for preparation of the design, specifications, and other documents to be used for procurement of goods to be purchased under this invitation of Bids.
- c) Bidders who fulfill the Eligibility Criteria mentioned in Chapter-2, clause-5, page No. 13 will be considered for Technical Evaluation of blds.
- d) Sidders should have proven capabilities in manufacturing, supply & installation of Doppler weather radars.
- e) Provisions of the Public Procurement (Preference to Make in India) order issued by the Department for Promotion of Industry and Internal Trade, Gowt. of India, vide OM No. 9-45021/2/2017-PP (BE-II) dated 4<sup>th</sup> June, 2020 and 16<sup>th</sup> September, 2020 shall be applicable in the tendering procees.
- f) As described in DIPP ON No. P-45021/2/2017-PF (BE-11) dated 15<sup>th</sup> June, 2017, "A supplier or bidder shall be considered to be from a country if (1) the entity is incorporated in that country, or ii) a majority of its shareholding or effective control of the entity is exercised from that country; or (iii) more than 50% of the value of the item being supplied has been added in that country. Indian suppliers shall mean those entities which meet any of these tests with respect to India."

#### 4. Tendering Expense:

The bidder shall bear all the costs and expenditure incursed and/or to be incurred by them in preparation, and in uploading their tender including attending the pre-bid conference and or arranging demonstration of Product/Services or Presentations that may be deemed necessary by IND.

# 5. Pre-Bid Conference:

a) Pre-bid conference shall be held as per Notice Inviting Tender (NIT) schedule so as to provide an opportunity to the bidders to interact with India Meteorological Department (IMD) with regard to various tender provisions/clauses, before the bids are submitted.

:5)

- (b) Request for clarification during pre-bid, if any, may be sent by email latest by five working days before the commoncement of pre-bid meating. Pre-Bid minutes shall be uploaded on e-procurement portal (sprocure.gov.in/eprocure).
- c) Bidders are requested to attend or may depute their authorized representative for pre-bid meeting.
- d) In case, due to the points/doubts raised by the prospective bidders, tender needs to be modified, the same will be considered for modification.
- e) No charge will be permissible after notification of prebld minutes
- f) No reply in this regard shall be sent to individual bidders.

#### 6. Regular inspection of website:

Prospective bidders are advised to see Central Public Procurement (CPP) portal **eprocure.gov.in/eprocure** on regular basis for any change in NIT schedule like amendment / corrigendum in Tender Document including technical requirement and pre-bid minutes etc.

#### 7. Amendments to Tender enquiry (TE) documents:

At any time, prior to the deadline for submission of tender, IMD may, for any reason deemed fit by it, modify the Tender Enquiry document by issuing suitable amendment(s) to it. The emendment will be uploaded on CPP portal eprdeure.gov.in/eprocure only.

In order to provide reasonable time to the prospective bidders to take necessary action in preparing their tenders as per the amendment, IMD may, at its discretion extend the date for submission of tenders and other allied time frames, which are linked with that date.

#### 8. Documents Comprising the Tender:

The tender is to be submitted in Two Bid System. The "Techno - Commercial Bid" and "Price Bid". It shall comprise the followings:

#### (A) Techno - Commercial Tender (Un-priced Tender)

a) The following documents are to be furnished by the bidder along with Technical Bid (Techno-Commercial Bid) as per the eligibility conditions applicable. Bidder shall upload following documents on CPP Portal eprodure.gov.in/eprocure



- b) Registration tertificate of Bidder with any state and central government body of India. Credential/document shall be attached.
- c) Checklist section (as per Annexure-I) properly filled and signed.
- d) Scanned copy of Earnest Money Deposit (EMD) in the form of Fixed Deposit Receipt/ Bank Quarantee (FDR/BG).
- e) Original EMD in physical form shall be submitted to Central Purchase Unit, Office of DGM, IMD, on or before opening of tender.
- f) Documentary evidence for fulfillment of Eligibility /Qualification criteria.
- (g) Tender terms 4 Conditions Acceptance Form (as per Annexure-11) duly signed.
- h) Technical Bid duly signed and stamped on all pages.
- List of deliverables (un-priced/without price) shall be submitted with details of model being offered etc.
- j) All should be similar to the items in price bid. Predontract integrity pact to be signed and provided along with bid document. (as per Annexure-IX)
- k) The above documents must be signed (all pages), stamped and scanned& shall be attached in the beginning of technical bid.

## (B) Price Bid (In separate envelop)

# Frice bid documents are to be furnished by the bidder as per following:

- a) All pages of the price bid should be page numbered, indexed and signed with company/firm's seal by authorized signatory.
- b) Price Bid shall be preferred as per price schedule format (Chapter-3).
- c) Costing of each and every item, sub item offered in bidder's technical bid, shall be done with all breakup prices.
- d) The bidder shall indicate on the Price Schedule specifying all components (main units and sub units etc. of each item) of prices shown therein including the unit prices and total tender prices of the goods (Mardware & Software), services, packing, transportation/freight/insurance to the sites, GST or any other duties and taxes applicable against the requirement.

- e) Contractor shall bear all the taxes (GST/IGST/SGST/Income-tax /WCT/or any other taxes) levied by the state / central government in force in India, as per the rates prevailing at the time of submission of tender in accordance with the Income-tax Act.
- f) Comprehensive Annual Maintenance Contract (CAMC) shall be for the maintenance of complete system including equipments and software therefore prospective bidders are advised to quote CAMC charges accordingly and specifically for seven years after the expiry of three years of warranty period. The charges are to be quoted for each year, on annual basis. Minimum amount shall not be less than 5% of the capital cost.
- (g) The reasonability of cost including the CAMC oberges shall be a criterion for deciding the lowest bidders. Justification of CAMC charges with breakup need to be submitted along with the bid.
- h) In case any charges for items are not mentioned in the price bid, it will be treated as all such items are free of cost.
- Vendors shall guote prices on F.O.R/FCA (at the sites of consignee)basis.
- If there is a discrepancy between the amount expressed in words and figures, the amount in words shall prevail.

Price bid shall summarily be rejected in case of any deviation from the un-priced bid given with the technical bid of the bidder.

Frice bids shall not be accepted if CAMC charges are quoted in percentage.

#### 9. Signing and Submission of Tender:

Properly signed and stamped tender on the company letterhead shall be uploaded online through CPP Portal, eprocure.gov.in/eprocure: Hard copy of bids shall not be anoepted for submission. The tender shall not contain any over writing. Only POP format of the tender shall be uploaded on CPP portal.

One set of hard copy of complete techno-commercial his document to be submitted before opening of the bid.

### 10. Alteration and Withdrawal of Tender :

Ver

- a) The bidder after uploading its tender on CPP portal is permitted to alter / modify its tender within the deadline for submission of tenders.
- b) Any discrepancy noticed in the hard copy and the soft copy of the bid submitted online by the bidder, the uploaded soft copy will be treated as final version of the bid for evaluation.

#### 11. Opening of Tenders:

IMB will open the tenders at the specified date and time and at the specified place as indicated in the NIT. In case the specified date of tender opening falls on / is subsequently declared a holiday or closed day for IMD, the tenders will be opened at the appointed time and place on the next working day.

Authorized representatives of the bidders, may attend the tender opening, provided they carry letter of authority from the respective bidders.

- (a) The Technical Bids are to be opened at the prescribed date and time. These bids shall be scrutinized and evaluated by the competent committee/ authority with reference to parameters prescribed in the TE document. During the Technical Bids opening, the tender opening official(s) may read out the salient features of the tenders.
- b) Thereafter, in the second stage, the Price Bids of technically qualified bidders only shall be opened on a date notified after evaluation of the techno commercial tender.

## 12. Scrutiny and Evaluation for acceptance of tender

(A) Scrutiny of bids:

The tenders will be scrutinized to determine whether they are complete in all respects and meet the essential requirements, conditions etc. as prescribed in the TR document.

The tenders are liable to be treated as non - responsive and will be summarily rejected if following are not essentially provided along with techno-commercial bids.

 a) Registration certificate of hidding bidder with any state and central government body of India. (Credentials/documents shall be attached).

- b) Tender should be signed, stamped and complete in all respects, All documents shall also be digitally signed.
- c) Properly signed and stanged checklist (Annexure-I) and fully completed compliance statement is to be enclosed.
- d) Tender Acceptance Form (Annexure-II) to be duly signed and stamped. (i.e. all the terms & conditions of tender document are acceptable).
- e) Tender validity for the required period.
- f) Required EMD to be provided.
- g) Copy of agreement of prime bidder from India with its foreign principal, if any, along with the precise relationship between them and nature of services which would be available from Frime Bidder in India, also to be attached with the tender.

#### (B) Technical Evaluation:

- a) After the tender has been accepted for technical evaluation, tenders shall be evaluated to assess the technical suitability of the bid with respect to the terms and conditions of the RFP, by the committee constituted by competent authority.
- (b) During the preliminary examination, if any clarification is required, IMD may ask for clarification from the bidders.
- c) Wherever necessary, IMD will convey its observation on such 'minor' issues to the bidder seeking bidder's response by a specified date. If the bidder does not respond by the specified date or provides evasive/incomplete reply without clarifying the exact point in clear terms, that tender shall not be considered for further processing.
- d) Technical presentation in the presence of the committee shall be held in IMD. The committee will seek proof of capabilities claimed in the compliance matrix provided by the respective bidder. IMD will seek clarifications on the design, performance and other technical points during the presentation. All points will be recorded.

## (C) Financial evaluation:

a) After Technical Evaluation, the Price Bids of only the technically qualified bidders shall be opened for further

10 and

scrutiny and evaluation on a date notified after completion of evaluation of the techno conmercial tender.

- b) IND shall evaluate the technically qualified financial bids for seciding lowest bidder (L-I) on the basis of <u>landing costs</u> of the store including all applicable taxes/levies/duties and installation and commissioning etc.
- c) The cost of CAMC charges etc. will be added to evaluate financial bid for deciding lowest bidder (L-1). Charges towards Insurance, Freight and transportation of goods up to delivery at sites atc. applicable. The cost of Warranty/ Extended Warranty not to be guoted separately. However, the cost of CAMC is to be guoted separately.
- d) IF ANY CHARGES ARE NOT INDICATED SPECIFICALLY AND SEPARATELY IN THE BID, SAME WILL BE TREATED AS INCLUSIVE.
- e) All the bidders must submit their financial quote in Indian rupees only.
- f) Purchase preference shall be given to all local suppliers in all producement undertaken by the Purchaser (IMD) in the manner prescribed by the Department for Promotion of Industry and Internal Trade, Govt. of India, vide OM No. P-45021/2/2017-EP (BE-II) dated 4<sup>th</sup> June, 2020. Purchase preference shall be given to Class I local suppliers in all producements undertaken by the purchaser in the following manner:
  - Among all qualified bids, the lowest bid will be termed as LL. If LL is from a "Class-I local supplier", the contract for full quantity will be awarded to LL.
  - · If Li bid is not a 'Class-I local supplier', 505 of the order quantity (this procurement being divisible in nature) shall be awarded to L1. Thereafter, the lowest bidder emong the 'Class-I local applier' will be invited to match the L1 price for the remaining 50% quantity subject to the Class-I local supplier's quoted price failing within the margin of purchase preference (20% as prescribed by DIPP OM dated 04.06.2020), and contract for that quantity shall be awarded to such 'Class-I local supplier' subject to matching the L1 price. In case such lowest eligible "Class-I local supplier' fails to match the L1 price or accept less than the offered quantity, the next higher 'Class-I local supplier' within the margin of purchase preference shall be awarded accordingly. In case some quantity is still left uncovered on Class-I local suppliers, then such halance quantity may also he ordered on the 11 bidder.

In case the TE document permits the bidders to quote their prides in different currencies, all such quoted prices of the responsive bidders will be converted to Indian Rupees for the purpose of equitable comparison and evaluation, as per the selling rate of exchange of State Bank of India prevailing on the closing date of the submission of bid.

# 13. Packaging and Marking:

The packaging for the goods provided by contractor should be strong and durable enough to withstand, without limitation, the entire journey during transit including transshipment (if any), rough handling, open storage etc. without any damage, deterioration etc.

## 14, Inspection, Testing and Factory acceptance test (FAT):

- a) IMD reserves the right to inspect goods at factory site/supplier site before their dispetch if required and mentioned in technical requirement (TENDER DOCUMENT) section.
- (b) FAT shall be undertaken by IND based on mutually appendie terms and condition.
  - c) Soods accepted by IMD/donsignee and/or its inspector at initial inspection shall in no way dilute purchaser's/consignee's right to reject the same later, if found deficient in terms of the clauses of the contract.
  - d) The equipment will be accepted subject to final inspection and test on commissioning and before handing over the equipment to consignee at the site.
  - e) During FAT, cost of travel, per diem charges and charges for poarding/loaging for IMD personnel (5 persons) will be borne by IMD, Government of India.



### CHAPTER-2

# Conditions of Contract (CoC)

Contractors shall accept all the terms and conditions of tendors including payment terms etc. Acceptance shall be unconditional and contractors shall have no claim and right in future on their terms if any.

Any Special instructions as per "filst of requirements/ technical specifications" section will also apply for this purchase.

The conditions (like qualification criteria, delivery schedule, mode of delivery & sites of delivery etc.) mentioned in "list of requirements/ technical specifications section" etc. will also apply for this purchase.

The date of installation of each Radar at 8 different places may vary and accordingly its commissioning date may very which will result in different warranty period and different CAMC period of all 8 Radars. This factor shall be taken in to account while devising the contract clause, warranty clause, CAMC clause and especially in the payment terms and conditions as mentioned in RFP.

NOTE: Whenever there is any conflict between the provisions in the CoC with regard to specific Para under "Chapter-3", the provision contained in the "Schedule of requirements, specifications 5 allied technical details" shall prevail and have an over-riding effect.

1. Tender Validity:

The tenders shall remain valid for acceptance for a period of 180 days (one hundred eighty days) after the date of tender opening prescribed in the TE document.

# 2. Purchaser's Right to accept any tender and to reject any or all tenders:

IMD reserves the right to accept in part or in full any tender or reject any tender without assigning any reason or to cancel the tendering process and reject all tenders at any time, prior to award of contract, without incurring any liability whatsnever to the affected Didder or bidders.

#### 3. Tender Fee:

No tender fee is charged on the downloaded and e-tenders.

## 4. Price preference:

- (a) Price preference shall be given to Micro and Shall Industries registered as manufacturers for Doppler Weather Baders equipment with National Small Industries Corporation or any other government agencies as per the latest guidelines/orders from Government of India.
- b) Purchase preference and guantity etc. shall be decided as per the Government of India orders.
- c) The binders shall have to upload and submit the copy of valid registration certificate. Micro and small Enterprises are exempted from submitting fees/cost towards tender document and submission of earnest money deposit (EMS), also known as security deposit.
- d) Micro and small Enterprises are not exempted for performance security or Bank Guarantee (BG) and have to furnish performance security if purchase order is placed to them. There is no relaxation in this regard.

#### 5. Qualification criteria for Bidders:

#### 1. Eligibility

The Bidder should not be blacklisted by any Central/State Government Department/Organization/PSU as on the date of submission of bid. Undertaking as per Annexore-XI of Chapter-5 to be submitted.

#### 11. Manufacturing capability

Along with all the necessary documents/certificates required as per the tender conditions, the hidder to furnish a brief write-up, backed with adequate data, explaining his available capacity (both technical and financial), for manufacture and supply of the required goods/equipment, within the specified time of completion.

Supporting documents submitted by the bidder must be certified and submitted as follows:

All copies of supply/work orders; respective completion certificate and contact details of clients; documents issued by the relevant industries Department /manufacturing license; annual report, etc.

### III. Creditworthy report

MIRA inform report of the bidder for the Current Financial Year is to be enclosed along with the Technical Bid. The minimum rating for Financial Qualification is Rating-Ba.

The Creditworthy Report may be obtained from:



M/s. MIRA INFORM PRIVATE LIMITED, 605, Palmepring, Near D'Mart, Link Road, Malad (West), Mumbal: 400 064; Tel Nos.: 022 - 40448000 (44 linus) Fax No. 022-0448045 / 40448046; E-mail: mira@mirsinform.com; <u>info@mirsinform.com</u> Website: http://www.mirainform.com

Note: The creditworthy report from other reputed and equivalent contractors (such as Dun & Bradstreet) is also acceptable. Nowever, report should have been obtained after 1"April, 2020.

#### IV. Experience and Past Performance:

The Bidder shall satisfy the following criteria to qualify during the last ten years from the date of submission of bid:

The bidder must have executed successfully supply order of value Rs. 20.0 Cr for similar radar as desired in the tender.

In support of experience, past performance and capacity/capability should be authenticated by the person authorized to sign the tender on behalf of the bidder, Original Documents must be submitted for inspection, if so demanded.

#### V. Financial Standing - under all conditions

Bidder should submit individual statement confirming compliance to all of the following with documents.

a) The average annual financial turnover of "The Bidder" during the last three years, ending on '11" March, 2030', should be at least eighty Erore (Rs. 80.00 Cr) per annum or equivalent in foreign currency, at exchange tate prevalent on the date of submission of hid. In this regard audited annual balance sheet and profit or loss statement/reports, duly authenticated (by a Chartered Accountant/Cost Accountant in India or equivalent in relevant countries) of last three consecutive years shall be submitted along with ternhical bid. The profit/loss statement should categorically indicate profit or loss for each year.

- [b] Bidder should not have suffered any financial lose for more than one year during the last three years, ending 31st March 2020.
- (c) The net worth of the bidder should not be negative on "The Bist March 2020 or latest last financial year" and also should have not eroded by more than 305 (thirty percent) in the last three years, ending on "The Bist March 2020 or latest last financial year".
- (d) In case of Indian Bidder who have been restructured by Banks in India, under the statutory guidelines, they would be deemed to have gualified the financial standing criteria considering the institutional financial backing available to them.

## VI. Applicability in Special Cases.

- a) Applicability under 'Make in India'
- (I) Bidders who have a valid/approved ongoing 'Make in India' agreement/program with Government of India and who, while meeting all other criteris above, would also be considered to be qualified provided:
  - Their foreign "Make in India" associates meet all the criteria above without exemption, and
  - ii. The bidder submits appropriate documentary proof for a valid/approved ongoing 'Make in India' agreement / program.
  - iii. The Bidder furnishes along with the bid, a legally enforceable undertaking, jointly executed by himself and principals, for manufacture, supply land erection, commissioning) and performance of the product offered including all warranty obligations as per the general conditions of contract.
    - (II) As prescribed by the Department for Promotion of Industry and Internal Trade, Govt. of India, vide OM No. P-45021/2/2017-PP (BU-II) dates 4<sup>th</sup> June, 2020, bidder shall be required to provide following (at the time of bidding) for verification of local content:
      - 1. The 'Class-I local supplier'/ 'Class-II local supplier' at the time of tender, bidding on solicitation shall be required to indicate percentage of local content and provide selfcertification (as per Annexure-XIII) that the item offered meets the local content requirement for 'Class-I local supplier'/ 'Class-II local supplier', as the case may be. They shall also give 16

details of the location(s) at which the local value addition is made.

2. In cases of procursments for a value in excess of Rs. 10 Crores, the 'Class-I local supplier'/ 'Class-II local supplier' shall be required to provide a certificate from the statutory or cost auditor of the company (in the case of companies) or from a practicing cost accountant or practicing chartered accountant (in respect of suppliers other than companies) giving the percentage of local content.

#### 6. Contact Details:

The complete name and address of the bidder along with permanent income tax account number (PAN) as allotted by the Indian Income Tax authority must be submitted.

#### 7. Earnest Money Deposit (EMD):

- a) The bidder shall furnish along with its tender, earnestmoney for an amount as shown in the tender notice.
- b) The bidders who are registered as Micro and small Enterprises specified by Ministry of Micro, Small & Medium Enterprises (MSME) for the specific item and services being procurat under this tender are exempted from EMS.
- (c) The EMD shall be furnished in Fixed Deposit Receipt (FDR) or Bank Guarantee (BG) (as per Annexure-III) from any Nationalized bank in India.
- (d) FDR may be issued in the favour of "DDG, G/o DGM, IMD, New Delhi", Bank Guarantee issued from the foreign banks must be authenticated by STATE BANK OF INDIA or any other Nationalized Bank of India. The clause "encashment/release of FDR/BG requires clearance certificate from Purchaser i.e. DGM, IMD must be mentioned in issued FDR/BG by Bank.
- (e) The earnest money shall be valid for period of sixty (60) days beyond the validity period of the tender.

#### 8. Refund of EMD:

- a) EMD of the unsuccessful bidders will be returned to them without any interest, after explicitly of the tender validity period.
- b) EMB of the contractor will be returned without any interest, after receipt of performance security from the contractor.

12

 c) Contractor shall submit pre-receipt for obtaining back their security.

## 9. Forfeit of EMD:

- a) Earnest money of a bidder will be forfeited, if the bidder withdraws or amends its tender or impairs or derogates from the tender in any respect within the period of validity of its tender or if it comes to notice that the information/documents furnished in its tender is incorrect, false, misleading or forged without prejudice to other rights of IMD.
- (b) The contractor's earnest money will be forfeited without prejudice to other rights of Purchaser if supplier fails to furnish the required performance security within the specified period.
  - c) Bidder shall have to extend the validity of EMD if extension of tender validity is agreed on the request of purchaser.

## 10. Performance Security:

#### A. Submission

Contractor shall submit performance security as per Annexure-IV, within thirty (30) days from date of dispatch of supply order/award of contract by IND or within twenty one (21) days from the receipt of supply order by contractor whichever is earlier.

- a) IMD may consider annulment/cancellation of supply order/ award of contract if performance security not received in stipulated time.
- b) There is no relaxation/exemption in submitting of performance security.
- c) Contractor shall furnish performance security to IMD for an amount equal to ten percent (10%) of the total value of the contract excluding CAMC, if any, valid up to sixty (50) days beyond the warranty period.
- d) For CAMC, the prime Bidder shall furnish performance security to IMD for an amount equal to five per cent (5%) of the total value of the CAMC, valid up to sixty (60) days after the date of completion of all contractual obligations of CAMC by contractor/service provider(TO BE SUBMITTED 30 DAYS BEFORE COMPLETION OF WARBANTY PERICE).
- Performance Security has to be submitted irrespective of its registration in NSIC etc.

- f) Performance security is not relaxed to any bidder.
- (g) Performance Security shall be in any one of the articles namely FDR or BG drawn / issued by a Nationalized bank in the prescribed form, in favour of IMO.
- (h) In the event of any amendment issued to the contract, contractor shall, within twenty-one (21) days of issue of the amendment, furnish the corresponding amendment to the Performance Security tas necessary), rendering the same valid in all respects in terms of the contract, as amended.

## B. Refund

IMB will release the already submitted valid Performance Security without any interest to contractor/service provider on completion of contractor's all contractual obligations including the warranty and CAMC obligations. Contractor shall submit pre-receipt for obtaining back their security.

## 11. Terms of Delivery:

- a) Goods shall be delivered by contractor in accordance with the terms of delivery schedule specified in the contract on FOR basis.
- (b) Suppliers should not deliver the goods after the valid delivery period unless a prior consent has been obtained from the competent authority of IMD and date of delivery extended in writing.

## 12. Delivery schedule:

- (a) As per "List of Requirements" under TENDER DOCUMENT-The Date, on which all the stores as per supply order have been installed and commissioned at all sites of IMS shall be treated as the final date of delivery of stores for calculating liquidated demages etc.
- b) Contractor is required to apply to IMD for extension of delivery period and obtain the same before dispatch. In case contractor dispatches the goads without obtaining an extension, in would be doing so at its own risk and no claim for payment for such supply and / or any other expense related to such supply shall be against IMD.

## 13. Force Majeure:

a) Force Majeure means an event beyond the control of contractor and not involving contractor's fault or negligence and which is not foreseeable. Such events may (b). 19 include, but are not restricted to, acts of IMD wither in its sovereign or contractual capacity, wars or revolutions, hostility, acts of public enemy, civil connotion, sabotage, fires, floods, explosions, epidemics, quarantine restrictions, strikes, lookduts, and freight embargoes.

- b) If there is delay in performance or other failures by contractor to perform its obligation under its contract due to event of a Force Majeure, contractor shall not be held responsible for such delays/failures.
- c) If a Force Majeure situation arises, contractor shall promptly notify IND in writing of such conditions and the cause thereof within twenty one days of accurrence of such event.
- d) Unless otherwise directed by IND in writing, contractor shall continue to perform its obligations under the contract as far as reasonably practical, and shall seek all reasonable alternative means for performance not prevented by the Force Majeure event.
- (e) If the performance in whole or in part or any obligation under this contract is prevented or delayed by any reason of Force Majeure for a period exceeding sixty days, the department may at its discretion terminate the contract without any financial repercussion.
  - There may be a Force Majeure situation affecting the purchase organization only. In such a situation the purchase organization shall take up with contractor on similar lines as above for further necessary action.

#### 14. Warranty:

- (a) The warranty shall be on-site warranty for 03 years. The guoted rate shall be deemed to be included in the guoted prices.
- (b) All supplied stores should be free from all defects and faults in material workmanship and manufacture.
- (c) Goods should be of the highest grade and consistent with the established and generally accepted standards for material of the type used and in full conformity with the specifications, drawings, or samples and shall, if operable, operate as per rated parameters mentioned in this RFP.
- d) Contractor shall be bound to furnish a clear written warranty for 3 years.
- (e) Contractor will be required to replace defective goods at site, free of cost inclusive of all freight and handling charges.

Perry 30

- f) Contractor shall provide warranty certificate from the GEM for the goods along with date of manufacture of stores/products.
- (g) Contractor shall take over the replaced parts/ goods after providing their replacements and no claim, whatsoever shall lie on IMD for such replaced parts/goods thereafter.
- h) Custom duty charges, if any, for re-export/re-import of defective parts/repaired parts or replaced parts to the foreign supplier country for repairs etc shall be borne by supplier only.
- Transportation cost for sending defective parts for repairs and sending back repaired or replaced one to IMO site(s), shall be borne by supplier itself.
- (j) Warranty shall be quoted as per IMD requirements i.e. three years after commissioning of the individual Radars, otherwise the Bid shall be considered as unresponsive.
- (k) Other condition, if any, under warranty clause of "List of requirements/ technical specifications" section shall also be applicable.
- The maximum down time permissible is 5-days in each quarter (90days), excluding period for preventive maintenance, for each radar. If there is a failure of the system for more than the criteria stipulated above then LD will be applicable at the rate of 0.5% per day (calculated for value of that station) and part there of subject to maximum of 10% of charges for that quarter.

## 15. Comprehensive Annual Maintenance Contract (CAMC) for Equipment and Software

- a) IMS/Consignee reserves the right to enter into Comprehensive Annual Maintenance contract between Consignee and Successful contractor after the completion of warranty period.
- (b) CAMC shall be for the maintenance of complete installation (including equipment and software). Prospective Bidders are advised to quote accordingly and specifically.
- c) Payment for maintenance contract is made on quarterly basis unless it is specified otherwise in the technical section.
- d) As per IMD requirements, year wise CAMC shall be quoted for 07 years after completion of 03 years warranty period, otherwise the Bid shall be considered as unresponsive. The minimum amount for each radar, shall

not be less than 5%, of the total cost of the complete system installed at respective sites.

# 16. Penalty clause/Liquidated damages clause (LD) for delayed delivery of stores & Services:

- a) Contractor shall deliver the goods and perform the services (delivery, installation, acceptance and commissioning) under the contract within the time achecule specified by IMD in the "List of requirements/ technical specifications" section and as incorporated in the supply order.
- (c) The delivery date shall considered as the date on which all the items/stores/materials/services etc., have been delivered as per Supply/Purchase order. Any delay shall be taken into account for penalty/LD purpose as per term/conditions of the contract.
- c) Penalty/Liquidated damages shall be calculated on the total purchase/contract price including the element of taxes etc., mentioned in the price bids.
- d) IMO shall, without prejudice to other rights and remedies available to IMO under the contract, deduct as penalty/liquidate damage from the contract price, a sum equivalent to 0.5% (half percent of cost of stores) per week of delay or part thereof on delayed supply of goods and/or delayed services in deviation to the milestone in Delivery Schedule, mentioned elsewhere in the document, subject to a maximum of 10% of the total contract value.
- e) L/D shall not he imposed under force majeure conditions.
- f) Once the maximum is reached purchaser may also consider following:
  - i. Forfeiture of the performance security.

id. Termination of the contract for default.

- iii, Black Listing of the firm; if the firm will not adhered the IMD terms and conditions of the contract.
- q) Contractor shall not be held responsible for delay in delivery of stores and their installation under the followings reasons:
  - Delay in providing Entry permits/Road Permits (if required) to Contractor by IMD.
  - Delay in providing proper site(s) by IMD to Contractor, for installation of stores;
  - III. Delay in providing No Objection Certificate (NOC): required from any other government agency/agencies.



Communication facility required for project to be provided to Contractor by IMD, if it is not the responsibility of supplier.

- IV. Due to delay in any or all of the above conditions the prescribed date of delivery shall be extended by the number of days of delay.
- (h) Contractor shall inform to IMD directly in writing regarding any delay on part of IMD.

#### 17. Award Criteria and Tolerance Clause:

- (a) The purchase order /supply order shall be awarded to the eligible responsive BIDDER tender, evaluated as the most economical, technically qualified and suitable to the requirements.
- (b) IMD reserves the right to increase or decrease the quantity of required goods up to twenty five percent (25%) till the placement of supply order without any change in the terms & conditions and prices quoted by the bidder.
- c) IND shall reserve the right to increase/decrease the ordered quantity by 25 (Twenty Five) percent at any time; till final delivery date (or the extended delivery date of the contract) at the same price with same terms and conditions subject to approvals from competent authority; by giving reasonable notice even though the quantity ordered initially has been supplied in full before the last date of the delivery period (or the extended delivery period).

#### 18. Modification of contract:

- a) If necessary, during the period of the contract, IMD may amend the contract, by making alterations and modifications within the general scope of contract and issue a written order in this regard to Contractor at any time.
- b) The successful bidder shall sign a contract/agreement with IMD as per terms and conditions specified in this RFP. The format of the Agreement will be provided after finalisation successful bidder.

### 19. Taxes and Duties in India:

a. Duties and Local Taxes:



#### 17564/2021/UAID DGMHQ

#### DGM-HQ-24014(11)/1/2021-UAID

- i) Contractor shall pay Work Contract Taxes (NCT), GST/IGST/SGST/ Service Tax and other taxes where applicable as per existing rules at that time, It shall be included in his cost so nucted.
- iii. Normally materials to be supplied to Govt. Department against Govt, contracts are exempted from levy of town duty, Octrol duty, terminal tax and other levies of local bodies. The local Town/Municipal Body regulations at times, however, provide for such exemption only on production of such exemption certificate from any authorized officer.
- iii. IMD is exempted from payment of local taxes/ levies i.e. town duty, Dotrol duty, terminal tax etc. Certificate for the same shall be issued to the successful contractor. However, in case, some department does not honour the certificate of IMD the contractor may make payment for the same and seek reimbursement from the department with prior information and written permission of IMD.
  - iv. Successful contractor shall pay the Outroi, entry tax etc. if exemption certificate not agreed by local authorities and same may be got reinbursed from purchaser on proof of payments to avoid delay in the supply of stores.

Note: All payments due under the contract shall be paid after deduction of statutory levies at source (like ESIC, IT (TDS), GST, LBT / Octroi etc.), wherever applicable.

b. Supply of Road Permits by the indenter /consignee:

In all such cases where the requirement of Road Permit for entry of goods into a particular State is mandatory, the following provisions shall be strictly followed:-

- Contractor shall request the indenter/consignee for providing Road permit within 10 days of the receipt of the Supply order.
- Contractor shall furnish all the necessary information and documents in this regard to consignee.
- iii. On receipt of the above request from Contractor, IND concerned shall arrange to provide the Road permit/way Bill in the prescribed form to Contractor within a maximum period of 20 days so that the same reaches Contractor before the dispatch of the stores.
  - iv. However, in cases where the Road permit/Way Bill is issued on proof of actual involce of the material, IMD

ENV 24

shall arrange to provide the Road permit/way Bill from appropriate authorities within a maximum period of 20 days from the secelpt of invoice.

V. Contractor shall not be held responsible for any delay in supply due to non- supply/delayed supply of Road permit provided he applies for it in time.

## c. Income Tax and service tax etc:

- Tax deduction at source (TDS) shall be done before making payment to Contractors as per existing law in force. The bidders may visit website of Income Tax Department of India for details of Tax Liabilities, Rules, and Procedures etc.
- Indian bidders shall provide their Permanent Income Tax Number (PAN), TAN and GST registration number as required.

20. Terms and Mode of Payment:

### a) Supply, installation and commissioning of the systems: -

### Psyment Terms:

Payment, as per term mentioned below, shall be made subject to recoveries, if any, by way of liquidated damages /penalty clause /TDS or any other charges as per terms & conditions of contract if not specified elsewhere in the document.

Foilowing documents shall be submitted by the successful contractor;

- a) Three copies of supplier's invoice showing contract number, goods description, quantity, unit price and total amount.
- b) Consignce Receipt Certificate in original issued by the authorized representative of IND.
- c) Copies of delivery Challan identifying contents of each package.
- d) Inspection certificate by the nominated Inspection agendy, if any. Insurance Cartificate.
- e) Final Acceptance Report from consignee.
- f) Sixty percent (60%) of total contract value will be paid after receipt of goods at site. Forty percent (40%) payment towards stores after successful installation, test runs, completion of training.

:25

commissioning and acceptance of the system at each site including the period of endurance test of individual site. Payment shall be made on site wise installation basis after the completion of work according to the above said 60-40 distribution.

## b) Payment towards Comprehensive Annual Maintenance Contract Charges:

- IND may enter into CAMC agreement along with the SLA with Contractor at the rates as stipulated in the contract, after warranty period of C3 years.
- The payment of CAMC will be made after satinfactory completion on quarterly basis as per TENDER terms doly certified by IMD.
- 111. Contractor shall send its claim for payment in writing, when contractually due, along with relevant documents etc., duly signed by authorized signatory with date, to IMDs.
  - Bills/invoices shall be submitted separately for stores and services.
    - w. The bidder shall submit particulars of his bank account required for making payments.
      - (a) Account Number (b) Bank Name (c) Branch Name
      - (d) Address (e) IFS c
- (e) IFS code (f) NICR No.
  - (g) Telephone No.
- (h) SWIFT code etc.
- NAMES OF CONTRACTORS OF CONTRACT

## 21. Termination of tender by IMD:

- a) From the time of submission of tender to the time of awarding the contract, if a bidder needs to contact IMD for any reason relating to this tender anguiry and/or its tender, it should do so only in writing.
- b) In case a bidder attempts to influence IMD in IMD's decision on acrutiny, comparison & evaluation of tenders and awarding the contract, the tender shall be liable for rejection in addition to appropriate administrative actions being taken against that bidder, as deemed fit by IMD.
- c) IMD, without prejudice to any other contractual rights and remedies scalable to it (IMD), may, by written notice of default sent to Contractor, terminate the contract in whole or in part, if Contractor fails to deliver any or all of the goods or fails to perform any other contractual obligation(s) within the time period specified in the contract, or within any extension thereof granted by IMD.
- G) In the event of IMD terminating the contract in whole or in part, IMD may produce goods and/or services similar to those cancelled, with such terms and conditions and in

such manner as it deems fit and Contractor shall be liable to pay IMD for the extra expenditure, if any, incurred by IMD for arranging such procurement.

e) If Contractor becomes bankrupt or otherwise insolvent, IMD reserves the right to terminate the contract at any time, by serving written notice to Contractor without any sumpensation, whatspever, to Contractor, subject to further condition that such termination will not prejudice or affect the rights and remedies which have accrued and / or will accrue thereafter to IMO.

## 22. Arbitration:

- a) If dispute or difference of any kind shall arise between INO and Contractor, the partles shall make every effort to resolve the same anicably by mutual consultation.
- b) If the parties fail to resolve their dispute or difference by such mutual consultation within twenty-one days of its occurrence, then, unless otherwise provided in "list of requirements/ technical specifications" section either IND or Contractor may give notice to the other party of its intention to commence arbitration, as hereinafter provided the applicable arbitration and conciliation Act, 1996 as amended from time to time.
- c) In the case of a dispute or difference arising between IMD/ Consignee and all suppliers relating to any matter arising out of or connected with the contract, such dispute or difference shall be referred to the independent arbitrator appointed by the Director General of Meteorology.
- d) The award of the arbitrator shall be final and binding on the partles to the contract.
- e) Each party shall bear its own cost of arbitration.

#### 23. Venue of Arbitration:

- a) The venue of arbitration shall be the place from where the contract has been issued, i.e., New Delb1.
- b) The contract shall be interpreted in accordance with the laws of India and jurisdiction shall be High Court of Ualhi.

## 24. List of Deliverables:

a) The bidder shall submit the final list of Deliverables as given at Annexare-VI for all the stores. Hardware, Software items, subunits etc and all other services

Viril

which bidder is going to offer in their vechnical proposal to meet the requirements under "List of requirement 4 Technical specifications" of this tender document.

- b) The list of Goliverable shell be same as submitted in the price bid.
- c) The price bid shall not be considered if it is not matching with the list of deliverable submitted with technical-commercial bid document.

Note: It is mandatory to mention the details of offered stores/ items.

## 25. Terms & Conditions of Comprehensive Annual Maintenance Contract (CAMC):

- a) The CANC includes all equipment installed at each site, equipment installed at control center and inclusive of all computers, peripherals, printers, radar and equipment spares, components, cables, connectors etc and radar related materials like UPS, DG, Radome, Tower, etc.
- b) The removed/replaced defective material becomes the property of Contractor and shall be removed from site.
- c) The CAMC clause will be applicable for control center and equipment at individual radar sites.
- d) The CANE will commence immediately after the expiry of the warresty period of 03 years.
- e) The comprehensive maintenance contract includes preventive and corrective maintenance and free replacement of all types of the defective parts/devices and consumables including oil and lubrication. Diesel for running DG sets will be provided by the department on as requirement basis.
- Contractor should submit a detailed CAMC plan including preventive maintenance schedule.
- (g) The Contractor shall provide the details of its call center meant for booking the complaints along with the contact numbers like mobile nos., phone nos., mailing address and names etc of its service engineers.
- b) The radar shall be decommissioned for a period of two weeks for annual preventive maintenance and upkeep in a cyclic mode.
- The Contractor's engineers attending to the system are required to make all entries of their work done and

28

corrective measures taken by them with their signatures in the log book kept with the Radar station.

- 3) Overall uptime of the system shall be at least 65 days in a guarter of 80 days.
- k) If there is a failure of the system for more than the criteria stipulated in (j) above then LD will be applicable at the rate of 0.5% per day (calculated for CAMC value of that station) and part there of subject to maximum of 10% of CAMC charges for that quarter.
- If the total failure duration (CONTINUOUS OR INTERMITTENT) extends beyond one month then the contract may be terminated at the discretion of competent authority of IMD and cost of its repair from alternate scarce will be recovered from the "Bidder" and performance security shall be forfeited.
- m) Maximum two weeks shutdown for annual maintenance shall not come under the clause.
- n) Radar down time due to external factors and severe natural calamity beyond human control shall exempt the penalty criteria as in clause (k) above.
- (0) Supplier shall deploy trained manpower at each site preferably Graduates in Engineering in Electrical/Electronics/Communication for operation and maintenance for round the clock support.
- p) Date of commencement of preventive maintenance period of the individual radars shall be fixed in consultation with IMB.
- q) The mode of payment will be guarterly and will be made after end of each quarter on the basis of satisfactory performance certificate from UAID, IMD at New Delhi.
- contractor shall ensure IMD for regular backups of all the software.
- (s) The Contractor is also required to restore the existing Software from the Backups whenever required.
- Contractor will also be responsible for configuring the networking components.
- b) CANC contract will be signed with a validity period of seven years and renewed annually based on satisfactory performance. If required, contract may be extended by IMD. However, IMD reserves the right to terminate the contract at any time by giving three months' notice, if the performance of the system or the services rendered by Contractor is not found to be satisfactory.

#### 17564/2021/UAID DGMHQ

#### DGM-HQ-24014(11)/1/2021-UAID

- v) The Contractor has to submit an undertaking that it will not use IND's data for any commercial purpose.
- w) Data of radar will not be copied or transmitted without permission from IMD.
- z) This contract shall be governed in all respects by Indian Lews.



# CHAPTER-3

# Schedule of requirements, specifications & allied technical details.

#### Special Conditions of Contract (SCC)

Supplier shall submit their bids for Eight (GS) numbers of X-Band Dual Polarization Doppler Weather Radars with Solid State Power Amplifier based transmitters.

#### 1. GENERAL REQUIREMENT:

The specifications described herein refer to X-Band (9300-9500 MHz) Dual Polarized SSPA based Doppler Weather Radar including all peripherals, hereafter referred to as "The System". The System shall be capable of detecting and estimating meteorological parameters of severe weather phenomena that cause widespread damage to life and property.

- a) All the DWR systems to have following latest state of the art facilities for smooth operation of complete radar system and its accessories:
  - i. Diesel generator of minimum 15 KVA or suitable capacity required for continuous operation of entire DWR system including cooling system, along with minimum 100 L capacity fuel tank. Diesel generator shall have automated switching on and off feature in the event of normal electricity failure and resumption with RMF panel.
  - 11. Two online UPSs, in redundant mode and each with minimum capacity of 10KVA each or suitable capacity required for continuous operation of entire DWR system, along with separate battery banks. Each UPS should have at least 30 minutes power back-up and should be capable of taking the full load of radar.
- iii. NTP clock based on GPS for system clock time synchronisation of the radar and the connected computers in the radar network.
  - iv. Communication hardware and accessories for data transfer to central location.
    - v. The system will have dual polarization capability by simultaneous transmission and receive in both linear Sorizontal and Vertical polarizations.


#### 17564/2021/UAID DGMHQ

## DGM-HQ-24014(11)/1/2021-UAID

- 132/203
- vi, The system shall have user selectable Single polarization and Dual polarization mode of operation.
- wii. Latest state of art computer system shall be used for the generation of data and its processing.
- vill. The entire operation of the System shall be fully computer controlled and remotely manageable.
  - ix. The tentative locations for installation of the systems are mentioned in Annexore-VIII.
    - X. Installation of radar system will be on steel tower structure fabricated using hot dipped galvanized steel, at site. The standard of the steel and fasteners shall be certified for use in saline environment specified in Indian standard specification manual and specified explicitly. The specification shall meet minimum IS2062:2011 E250 Grade-C Steel for Channels and plates and IS1161:2014 & IS10748:2004 YST 310 grade steel for hollow pipes, IS1367 Grade8.3 for fasteners from reputed manufacturers and their details also shall be submitted.
  - xi. The lower structure shall be with height of 20m above the base or platform of the tower.
  - xii. For evaluation of tender, dost of the tower will be considered.
- kill. Appropriate cemented reinforced concrete base 60 cm thick shall be provided.
  - wiv. The quoted seftware should be in use in any operational weather services in the world to fulfill the functional requirements along with capabilities which have been specified elsewhere in detail.
    - .xv. At the time of supply of the stores, the latest state of art computer system and latest version of software shall be provided for the generation of data and it's processing, with OEM Licensed Version of Linux / Windows Operating System.
  - xvi, All equipment shall be of industry standard so as to enable easy up-gradation and maintenance.
- svil. Manufactures shall submit the full details of the hardware, including model numbers and the software proposed to be employed for meeting the requirements given herein.



- xviii, Central server at Delhi for processing the radar data from all eight radars to be provided.
  - xix. Facility for radar data analysis and products generation at each of the sites inclusive of automatic dissemination of warnings and alerts are to be provided by the bidder.
  - xx. Display of data such as reflectivity, rainfall rate, horizontal winds at designated height, warnings etc., to be overlaid on GIS map.
  - xxi. Web access to GIS based radar data display to be provided using web browsers such as Microsoft Internet Explorer, Firefox, Chrome etc.
  - wx11, GIS based display should be accessible over the network through VPN or Internet.
- Extlit. The contractor has to clearly specify the way of achieving the sensitivity & detection capability (with ref, to OVSPALL SYSTEM REQUISEMENTS) with supportive documents of claim and appropriate calculations for SSPA transmitters. The calculations for achieving the required operational characteristics such as scanning capabilities, maximum range, maximum velocity, sensitivity and slutter suppression have to be provided. Confirmation with with supporting images, test printouts etc., are to be provided.
  - XXiv. Lightning protection is to be provided for ensuring safety of the system and all tower mounted elements by way of grounding cable inrodgh ground bar or other best suited mechanism (grounding of tower shall be independent of grounding of its equipment and DG set).
    - xxv. The supplied DG Set, UPS etc., should have AMC service support facility in India.
  - xxv1. IMD will take possession after appropriate test and evaluation meeting the specifications and accept the radar system after commissioning.
- xxvii. It is the responsibility of the hidder to bear all the expenditure to operate the radar including manpower requirements, security and all radar peripherals till successful acceptance and commissioning.
- xxviii. Transportation from the factory to the site will be the remonstbility of the vendor.
  - xxix. The entire work of installation and commissioning of the radar has to be carried out by the contractor.



382

34

- xxx. The network link between the systems and central server will be provided by IMD; however the successful contractor shall suggest suitable bandwidth for real time system control, monitoring and near real-time receipt of data at central locations for generating composite images and products of all the radars.
- b) The price bids of only technically qualified Bidders shall be opened for evaluation on a date notified after evaluation of the techno commercial bid.

IMD shall evaluate the price bids of technically qualified vendors for deviding lowest bidder (L-1) on the basis of total landed cost at site including cost of all the deliverables as per tender document and all prevailing taxes and duties and any other charges as demanded by the vendor.

#### 2. OVERALL SYSTEM REQUIREMENTS:

IMO requires X-Band Dual Polarized Doppler Weather Radar Systems with SSPA based transmitter as mentioned in Table-1

		General
2.1	Range of observation	100 Km (Reflectivity) 100 Km (Velocity, Spentrum Width)
2.2	Range resolution	150 m or better
2.3	Max. Unambiguous Range	100km or better consistent with PRF & 2 <sup>nd</sup> trip echo.
2.4	Unambiguous Velocity	30 m/s or better with ambiguity resolver
2.5	Detection capability	13 d82 or better at 100 km range
2.6	VSWR	1,25:1
2.7	Scan Time	10 elevation volume scan with all base moments acquired in Sminutes or better
		Transmitter
2.8	Transmitter Type	Tunable Power Solid State Power Amplifier based system
2.9	Frequency Range	9.3 GHz - 9.5 GHz
2.10	Transmitted power	Required to meet 13 dBz at 100 Rm as per Foint No.2.5.
2.11	Pulse repetition	To meet Bange And Volgetty repulsioners

## TABLE-1: Technical Specification

# 17564/2021/UAID DGMHQ

# DGM-HQ-24014(11)/1/2021-UAID

	frequency	as per Points No. 2.3 &2.4
2.12	Pulse width	SSPA based system to meet the average power at variable pulse of transmissions at different carrier frequencies as per 2.5
2.13	Transmitter	STAR
2.14	Modulator	Set to at at at a
2.15	VSWR	1,25:1
s=it	Ant	enna, Radome Tower
2.16	Antenna	Parabolic Dish Antenna
2.17	Side lobe	26dB down from the main lobe to 12° and beyond 12° better than 30d3.
2.18	Beam width	1° or better
2.19	Azimuth steering	360" with 10.05" accuracy and 0+6 rpm
2.20	Vertical	-2" to +92" or better with ±0.03"
NAVISALA	Steering	#GGUTAGY:
2.21	Polarization	Horizontal, Vertical and STAR mode
2.22	Scanning rates	Op to 6 cpm
2.23	Scan strategy	Provision for automatic changeover between different scan strategies shall be possible.
2.24	Radone	<ol> <li>Type: Rigid spherical in shape (curves panels) installed on gelvanized steel Tower covering antenna dish and pedestal, with adequate space for maintenance personnel to enter and work.</li> </ol>
		2)Transmission Loss : 0.2d3 or better one way
2.25	Wind load	Up to 159 km/hr and in gusting condition up to 250 km/hr
2.26	Lightning Protection	Lightening rod with dual ground wires.
2.27	Obstruction lights	Twin Light System with solar powered Sauto switch with long life lamps. Roof Natch for maintenance of obstruction lights and entry from bottom; suitable portable ladder for the purpose of maintenance.
2.28	Tower height	29m
1		Receiver
2 20	Tama	Multichannel Digital receiver for Dual

# 17564/2021/UAID DGMHQ

# DGM-HQ-24014(11)/1/2021-UAID

2,30	Noise figure	3 dB or better				
and Address	Linear dynamic	2 95dB or better				
2.31	range					
2.32	Minimum Discernable Signal	-107dBm or better				
	Stanat					
	R	adar Signal Processor				
المددة الع	Doppler	Folse Pair and FFT selectable				
2.33	processing	annanara a shanan kanimadeda - casanasansansa				
2.34	Clutter suppression	Clutter Elimination for >45 dB. The system shall have provision for identifying an filtering non-meteorological echoes such a anomalous propagation echoes, Sea clutters bird/insects, chaffs, etc. based of polarimetric measurements.				
2.35	Range Side lobe	Setter than 35dB				
2.36	Parameters to be measured and displayed	<pre>(a) Reflectivity (Z<sub>b</sub>) • Dynamic range : -30 to 65 dBZ • Resolution : 0.1 dB Accuracy : SidB § SNR&gt;10dB ; r&lt;100Km:∆r&lt;1Km (b) Radial velocity (V<sub>a</sub>) • Max : ±30m/s • Besolution : 0.1 m/s Accuracy : S1 m/s §SNR &gt;10dB; o<sub>x</sub>=4 m/s ; r= 100 Km; ∆r&lt;250m (c) Spectrum Width (o<sub>a</sub>) • Max : ±15m/s • Resolution; 0.1 m/s Accuracy: S2 m/s §SNR &gt;10dB; o<sub>x</sub>=4 m/s ; r 100 Km; ∆r&lt;250m</pre>				
		<ul> <li>(d) Differential reflectivity(Z<sub>DE</sub>)</li> <li>Dynamic range : -5 to 8 dBE</li> <li>Resolution : 0.1 Db</li> <li>Accuracy :≤ 0.2dB @ SNR&gt;10dB : r&lt;100Km</li></ul>				

36

		<ul> <li>Bynamic range : 0 to 1</li> <li>Resolution : 0.005</li> <li>Accuracy:≤0.050SNR&gt;10dB;r&lt;100Km; Δr&lt;1Km</li> </ul>
		<ol> <li>Provision shall be made for programmable and auto run mode of internal calibration to ensure reliability of polarimetric parameters.</li> </ol>
2.37	Calibration	(II) Calibration through external equipment and validation of receiver linearity and dynamic range using standard coherent source and standard measuring equipment. There should be a provision for automatic update of radar manameters.
		<ul> <li>a) Receiver single point calibration in long and short pulse mode</li> <li>b) Transmitter peak power</li> <li>c) System noise figure</li> </ul>
2.38	Sun calibration	Sun valibration in both software driven and nanual mode operation for pointing accuracy neasurements. The system shall be made to point towards sun for establishing the gain and pointing accuracy of the antenna; stability and reliability of receiver chain using solar flux (sun) values known from other sources. Procedure shall be provided and to be demonstrated during SAT, Script based execution of such measurements and saving of results are expected as a part of such provision.
2.39	Base Parameters to be measured	<ul> <li>a. Reflectivity (2),</li> <li>b. Radial velocity (V),</li> <li>c. Spectrum Width (a),</li> <li>d. Differential reflectivity(Z<sub>00</sub>),</li> <li>e. Specific differential phase (K<sub>00</sub>),</li> <li>f. Differential phase (Φ<sub>00</sub>),</li> <li>g. Cross correlation Coefficient (p<sub>00</sub>)</li> <li>h. Linear Depolarization Ratio (L<sub>000</sub>)</li> </ul>
2,40	Peripherals	a) Two Workstations (Main & Standby) of latest computer configuration at the time of delivery in terms of mother board chipset, Processor, processor speed, 128 GB RAM size and speed, Ethernet speed/USB speed, HDM1/VGA/DV1 card memory and 4 TB hard disk storage with 32" (inches) full UHD resolution, color LED monitor. Both Workstation/

37 MY

		<ul> <li>the radar; product generation and display of the data and shall have Kaid Storage of the data to avoid any loss of data.</li> <li>b) Two workstations of latest configuration at the time of delivery in terms of mother board chip-set. Processor, processor speed, 128 GB RAM size and speed, Ethernet speed/USB speed, HUMI/VGA/DVI card memory and hard disk storage processor with 32" (inches) full UHD resolution, color LED monitor. Both Workstations shall be used for networking/communication purpose.</li> <li>c) One portable computer (laptop) of latest version/ configuration capable of handling function of a) and b) above.</li> <li>d) One 50" (inches) UHD WK LED display.</li> <li>e) Two deaktop computer of latest configuration processor at the time of delivery for analysis of radar data products.</li> <li>f) NAS storage with SAIO with archival for 05 years of base products as in 2.38.</li> <li>g) Provision for remote radar control, monitoring and operations.</li> <li>i) All software licenses shall be multiuser and oper, within radar group without any restriction/hardware lock / soft-lock.</li> </ul>
	副销售	Rover Reminements
2.41	Power	Capable of operating at 220 110% V, 50 12% Hz, in Single phase or 400 110% V, 50 12% Rz, with three phase AC supply.
		Two UPSs, in redundant mode and each capacity of at least 10 XVA, on Hine type,

2.42	Online UPS	to run the whole radar system for at least 60 minutes. Catering to required voltage stabilization with a power factor suitable for the radar system.
2.43	Diesel Generator	At least 15 RVA suitable Diesel Generator Set with AMF panel for automatic turn GN when mains fails and capable to takes up the load (of all the essential components

		and accessories of the Radar system required for operation). The DG set should be silent with a separate canopy for operations in all weather conditions.
2.44	Pre-fabricated cabia.	A well-furnished cabin of at least area 900 sq. feet is required to meet all operational requirements which includes operational room, Radar Officer room, UPS, stores, Kitchenette, microwave oven, Best room/Washroom, along with ACs, water cooler, RO, furniture and separate outside canopy housing for D.G. set etc. to make it convenient for operational staff to work round the clock. The number of floors and dimensions of cabin may vary in size from site to site.

#### 3. ARCHIVAL OF RADAR DATA:

- a. The base data which includes Reflectivity, Velocity, Spectrum Width and Dual Fol, Parameters (output of radar processor) shall be stored automatically on hard disk. Network Attached Storage on RAID 5 with adequate capacity based on SATA disk, to be provided for archival of Base Parameters data.
- b. A-4 size high resolution lnk tank Color Printer (600dp) or bigher) for taking hard copies of images and products shall be provided.
- c. External Blue ray DVS writer with 12 disks of dual layer Blue ray DVD R/W and 55 disks of Blue Ray DVD/R at each site to be provided.
- Provision to record, store and offline playback for analysis of 140 data.
- e. While disposing the data disk (Hard Disk) it should be destroyed so that data cannot be retrieved. The Annual Maintenance Contract with service providers should include a clause that Hard Disk should be retained by the organization (IMD), even if it is faulty.

## 4. DATA FORMATS:

## 4.1 Digital Data

 a) System should be capable of archiving of raw data II 4 Q) and generating Polarimetric Doppler Weather Radar Base

39

data and preducts in BUFR, NETCOF, GRIBZ, HDF5, KML, KM2 formats and NEXRAD-Level II formats.

- b) Data should be converted from RAW, RAINFALL mm/hr, RAINFALL ACCUMULATED in mm, Horizontal winds at user selected levels in height, to Cartesian coordinates, Such data should also be available in HDF5, NetCDF.
- c) Stand-alone BUFR, NETCOF, HDFS, GRIB2, NexRAD-Level II encoding and decoding software on Licensed Linux/MS-WINDOWS platform should be provided. The software should be able to convert the radar data to formats as per user requirements and IMD specifications montioned at 4.1(a) above.
- d) NetCDF format data shall be provided in NCAR CFRadial, and IMD-NetCDF format. Details of IMD-NetCDF format and BVFR-OPERA format file as required by IMD shall be provided to contractor for developing software applications.
- e) Existing central server system at IND HQ, New Delhi is based on Vaisala (SIGMET) IRIS software for centrally generating various products including mosaic and various data formats from NAW datas data products. The contractor should provide necessary provision to ingest their radar data in a compatible format for use with already available central server at New Delhi.
- f) Data format if proprietary should be disclosed with decoding software codes;
- g) The contractor shall provide data format converter to convert Raw Bata as well as products to ASCII.

## 4.2 Image data

The system should be capable of automatic generation of images in (JPEG, GIP, TIFF, PNG) format files for publishing on web site. Images should have high resolution for full RD displays and also for web pages. Following file naming conventions are to be implemented for automatic generation of images after completion of each volume scan.

a) cas\_stm.gif Max 2 100 km range
b) pps\_stm.gif PPI 2 100 km
c) pps\_stm.gif PPI 2 100 km
d) ppv\_stm.gif PPI V 100 km
e) vp2\_stm.gif VVP 40 km Range/ up to 10 km height
f) sri\_stm.gif SRT 100 km
g) pac\_stm.gif PAC 100 km accumulated rain for 24hrs

5. SOFTWARE FEATURES:



The radar system shall have required menu driven software with GUI controls for:

- a) Operating the radar.
- b) Secup of operational scan parameters:
- c) Configuration of weather products.
- d) Generation of alerts and warning,
- e) Setup of communication channels.
- f) Setup of display overlaid on map of India with political boundaries of international borders, states and district boundaries.
- g) Automatic calibration for antenna, receiver, dynamic range, etc.
- h) Monitoring the health of the radar using BITE.
- The process of setup/change of various scan parameters should be easily accessible to operators using GUL.
- j) Product generation;
- k) Product display.
- Generation of audio-visual warnings based on user defined thresholds for severe weather detection.
- m) Automatic transmission of warnings (visual and text) to users via communication channels.
- n) Facility to reprocess and display products from past data.
- a) Simultaneous display of data having more than one parameter.
- p) Requisite software protection for danying unauthorized access to be provided.
- q) The system shall perform optimized correction of reflectivity data for attenuation effects from heavy rain based on algorithm using polarimetric parameters such as 2DR,  $\Phi_{D2}$ ,  $R_{D2}$  and  $\rho_{ev}$ .

IMPORTANT NOTES:

I. The System shall be capable of generating the following products from the base data output from the radar signal

42

processor. Algorithms and references for all the products listed below and supplied should be provided.

II. The licenses of all softwares being installed with the radar system shall be in the name of Director General of Meteorology, IMD or any competent authority and the details of all softwares used in the radar system should be mentioned.

## 5.1 Base Products

- a) Un-filtered I & Q data archival and playback facility to generate base products.
- b) The system shall generate base data comprising of Z, V, o and Polarimetric products after applying different corrections to raw data (like attenuation effect due to precipitation, earth curvature, range normalization, beam blockage, interference due to external sources, nonmeteorological echoes, second-trip recovery, ground reflection, bright band correction, etc.)
- c) Products are to be generated based on user defined parameters already selected and stored in workstation and NAS against the various scan schedules.
- d) Provision also should be available to generate all products in offline mode using the archived raw data.

## 5.2 Primary Products

## 5.2.1 Maximum Display (Z,V,G)

The System shall compute and display maximum values of base data products (2, V and 0) in horizontal (East West and North South) and vertical columns between users defined heights and also display the partial images in a single frame with side panel heights to a scale of 2km covering 0 -18 km.

## 5.2.2 PPI (Plan Position Indicator) $(\Sigma, \forall, \sigma)$

The system should be capable of generating the PPI product for all types of raw data at user selectable elevation angles from lowest to highest elevation in the scheduled scanning procedure.

## 5.2.3 CAPPI (Constant Altitude Plan Position Indicator)

The System shall interpolate from the volume scan data set for a geo-horizontal glane at user vertical defined height and display the same pertaining to user selectable data form 2, V and o from I km to 18 km beight.

# 5.2.4 PCAPPI (PSEUDO CAPPI)

The system shall incorporate data form the highest elevation scan near the radar and from lowest elevation scan for areas far away from the radar for which radar beams are not.

42

intersected by user defined plane for CAPPI and display same pertaining to data selected by user (3, V and c) from 1 km to 18 km height.

### 5.2.5 VCUT (Vertical Cut)

The system shall interpolate all the base products (2, V and 0) in any vertical plane passing through user defined two points and display the same for the user selectable parameters.

# 5.2.6 EBASE (ECHO BASE)

The system shall identify from the volume scan data the minimum height up to which the user defined threshold value for each base data exists and display them for user selectable data.

## 5.2.7 ETOP (ECHO TOP)

The system shall identify from the volume scan data the maximum height up to which the user defined threshold value for each base data exists and display them for user selectable data.

### 5.2.8 HAIL WARNING

Hased on reliable hail warning algorithm, the system shall generate a hail warning symbol at the appropriate place in the PPI display in one or more of the operator chosen fields.

## 5.2.9 HYDROMETEOR CLASSIFICATION

The system shall be capable of generating a product for classification of hydrometeons based on Polarimetric parameters ( $Z_{200}$ ,  $\Phi_{220}$ ,  $B_{000}$  and  $g_{000}$ ). Provision for changing parameters in a scientific way for customization of the hydrometeor classification is a required. Hail detection based on this classification shall be one of the products in this class,

#### 5.3 Derived Meteorological Products:

#### 5.3.1 Velocity Products

The system shall generate and display following velocity products:

- a) Radial velocity versus the azimuth for a fixed elevation and a fixed slant range (VAD).
- b) Radial velocity at a fixed user defined range on height and azimuth angles (Radial velocity display for fixed range, azimuth angles for various height and azimuth).



- c) Registential wind velocity and wind direction using barbs in a vertical column above the radar site for different heights including divergence s convergence product. (VVP\_1)
- d) The vertical Profile of the horizontal winds derived from the Radial Winds within 40 km range of radar and 10 km height using standard algorithm in the form of Wind Barba showing wind speed and direction in the time series manner for a user selectable time duration (VVP\_2)
- e) Rerizontal wind vectors (UWT) using barbs at user defined layer height with or without underlay of reflectivity or velocity in PPI / CAPPI format.

# 5.3.2 Hydrological Products:

The system shall generate and display following hydrological products:

- a) Raiofall intensity using polarimetric moments as well as 2-R in a user selectable surface layer and constants with constant height above ground. Provision of specifying freezing layer height dynamically.
- b) Instantaneous estimation of water content (VIL) residing in a user defined atmosphere layer in the atmosphere to be displayed in PPI type of display.
- e) Precipitation accumulation (PAC) using polarizetric and Z-R in a user definable time period.
- G) Rainfall amount in user defined catchment basins for user defined time span.
- e) Provision for putting river basin map overlay as per user requirement.
- f) Rainfall intensity, rainfall rate and accumulation products shall have an option to be adjusted in real time by Rain Gauge, disdrometer data. Rain gauge and diadrometer data shall be displayed along with the radar data.
- Q) Adjustment of rainfall rate by appropriate rain gauge or disdrometer data shall be possible.
- h) The system shall convert data of reflectivity and polarimetric measurement to horizontal maps of rainfall intensity.

My My

4.6

- The system shall be capable of generating precise rain rate information using combination of polarimetric parameters as well as Z(h)
- j) The system shall use algorithm based on polarimetric parameters for correcting rain rate estimation errors arising out of hall, non-meteorological echoes and attenuation.

# 5.3.3 Aviation Products

- (a) The system shall evaluate derivatives of wind velocity in radial, azimuth, elevation, North South, East West directions and derive herizontal, vertical and three dimensional shears
- b) The system shall also be able to generate warning product on microburst, and wind shears beyond adaptable threshold levels:
- (c) The system shall evaluate maximum turbulence within user defined atmospheric layer and display in top view.

# 5.3.4 Warning and Forecasting Products:-

- a) System shall generate and display warning symbols for thonderstorm, hail storm, dust storm, meso-cyclone, obsvergence, divergence and gust fronts.
- b) System shall be capable of evaluating speed and direction of movement of weather systems.
- (c) System shall also be capable of warning if any of the conditions defined by the user are reached or fulfilled on reflectivity, velocity, VIL, rainfall intensity, rainfall accumulation and wind shear.
- (d) System shall be able to detect tornado and gust fronts associated with storms and issue visual and text warning message.

## 5.4 Alphanumeric Products

The system shall also be able to provide all the product data (i.e. base, primary and derived) in ASCII tabular form.

## 6. Built In Test Equipment (BITE) .

A modern system making use of latest technology for continuous monitoring of the operational status of

W 45

hardware and software functions and utilities of the radar system shall be supplied.

- a) BITE processor shall measure and process a number of real time analog and digital parameters in the radar system and generate and display the error message whenever their value falls outside the specified permissible range.
- b) BITE processor shall continuously monitor input and output signals of every module/PCB for any deviation from the standard values.
- c) Audio elerm indication for occurrences of faults is to be provided.
- d) Centralized monitoring of status of radars networked.

## 7. Provision for Networking & Communication system for data transfer to central location:

- a) Provision shall be made with suitable communication hardware & software for real time transfer of digital radar data and images generated in real time through networking to control and monitoring centre and central server at IMD HQ, New Delhi.
- b) All networking components required at radar site as well as command and control centre shall be provided by contractor.
- c) Necessary interface shall be provided for sending radar data through GSN, NPN and internet.
- d) The control centre should be able to monitor and control the functions of the radar at all eight sites. Data from respective radars under each site will be utilized for real time display facility for monitoring the health parameters as well as the weather data acquired by radars in operational mode.
- e) The communication link will be provided by IMD. contractor shall specify the bandwidth requirement.
- Deliverables for control and dommand dentre are to be provided as per Annexure-VI.
- g) The radar data is to be converted in a compatible format for use with already available central server of the existing Doppler weather radar network of IMD based on INIS (SIGMET) software of M/S Vaisala.
- b) Boundary of states will be provided by IMD as shape files. Data of all radars to be overlayed on GIS map with option to include underlay maps from Google, Open street map or ESRI, Arc GIS, etc. GIS server with Open street map to be provided.

46

The Products which are to be everlayed are:

- Reflectivity
- R4252811
- Warnings based on Rainfall, Velocity, Hydrometeor Classification.

## 8. INSTALLATION:

All installation related work including civil work shall be carried out by contractor. However, TMD personnel shall be associated with the installation process. All installation materials required shall be supplied by the successful contractor.

- a) The contractor shall take into consideration that the system is required to be installed on site on a Galvanired Steel Tower mounted on appropriate cement reinforced concrete base 60 cm thick with nominal height of 20 m upon which radar antenna and radope shall be mounted. Towers should be able to take the dynamic load of the radar system and its accessories while in operation, (with due consideration for the gusty wind load) and shall be erected by the contractor.
- b) Walk/inspection space of about a meter width all around the radone base with a safety railing of 1.5m height is to be provided for servicing of Radome. The railings should not degrade the signals of the radar during regular operations.
- c) The entire responsibility of civil construction/site preparedness for installation of the radar and its peripherals shall be the responsibility of the contractor.
- d) Pre-requisite for both civil & electrical requirements for installation of radar shall be clearly mentioned separately, inclusive of suitable diagrams of antenna & radome installations, along with the technical bid.
- e) The required number of electrical earthing based on latest technology i.e. Chemical Gel earthing is required for various peripherals inclusive of radar, has to be provided by the contractor.
- f) Suitable lightning Arresters for protecting the radar with reliable lightning protection system with deep chemical gol and copper plate based earth pit shall be

Mh 47

carried out by the contractor. The earth resistance shall be tested.

- (g) Aviation warning indicator lamps shall be supplied and installed by the contractor on the top of the antenna/radome at appropriate height.
- b) All other requirements such as power and communication facility etc. will be arranged by contractor for snabling tower construction and installation/ commissioning of radars of each respective site. However, after installation /commissioning of the radar systems at each respective site IMD will arrange the power and communication facility etc. for operational requirement.
  - INO shall not facilitate the accommodation and transportation arrangements for the personnel of the installation team of the contractor.

#### 9. LOCATION:

list of tentative altes for installation of Radara is attached vide at Annexore-VITL.

### 10. TESTING AND ACCEPTANCE:

- a) The successful contractor shall submit detailed testing plans for Pactory Acceptance Testing (FAT) prior to shipment and Site Acceptance Test (SAT) after installation at site for system acceptance. The test plan shall require concurrence of IMD.
- b) During the FAT, cost of travel, per diem charges and charges for boarding/lodging etc. for IMD personnel will be borne by IMD, Government of India.
- c) The objective of the tests shall be the verification of performance of the system as per the specifications and functional requirements as per TENDER DOCUMENT.
- d) As per the notually agreed test procedures, FAT shall be carried out at the factory premises prior to shipment. The equipment shall be shipped only after satisfactory conclusion and acceptance of the pre-shipment acceptance testing (FAT).
- e) As per the mutually agreed test procedures, acceptance test should be carried out at each radar site after installation. The contractor shall arrange for necessary test equipment, man-power etc.
- Any defect/ deviation noticed during the site acceptance tests shall be rectified within a maximum period of one

68

month from the completion of the tests. After such rectification, the tests shall be repeated to verify the rectlfication.

(g) Within 30 days of installation of each system, the contractor should secure acceptance of the radar and its peripherals as a whole system.

#### 11. SYSTEM COMMISSIONING:

After satisfactory completion of the site acceptance tests, the contractor shall demonstrate the reliabilities and capability of the system to be operated continuously and satisfactorily for a period of 15 days endurance test of the complete radar system, after which it will be said to be "Commissioned".

# 12. WARRANTY:

- a) Warsanty shall remain valid for three years after the system has been commissioned and accepted by the purchaser as per terms of the contract. The warranty shall also include all third party bought out items / subsystems including Tower, Computers, Generator Set and UPS, etc. OEM certification of warranty for the third party items is to be provided. They shall also be included in the overall performance of the system.
- b) This warranty clause is applicable at all individual radar sites.
- c) Upon receipt of notice about faults, the contractor shall repair or replace the defective goods or parts thereof, free of cost, at the site within 03 days.
- (d) The contractor shall take over the replaced parts/ goods after providing their replacements and no claim, whatsbever shall lie on the purchaser for such replaced parts/ goods thereafter.
- e) The contractor shall supply the software updates, if any, during the warranty and CAMC period, free of cost.
- f) Contractor shall ensure 95% of 36% days annual-uptime.
- (calculated Quarterly at the time of payments) and there is a failure of the system for more than the criteria stipulated, then a penalty amount of 0.1% of the total equipment cost per day for that radar, for days it is down, will be deducted from the performance guarantee amount, subject to an upper celling of 10% of the total equipment cost. Furthermore the purchaser may proceed to take such remedial action(s) as deemed fit by the

/ 荷見:

purchaser, at the risk and expense of the contractor and without prejudice to other contractual rights and remedies, which the purchaser may have against the contractor.

- (b) Maximum two weeks shutdown for Annual maintenance shall not come under the clause. Delay due to external factors and natural calamity beyond human control will be exempted.
- i) During warranty period, the contractor is required to visit consignee's site at least once in three months commencing from the date of adceptance at site for preventive maintenance, calibration and various types of checks of the goods/ equipment and a detailed report consisting of all test procedure values etc. must be submitted at Opper Air Instrument Division (CAID), India Meteorological Department, New Delhi along with satisfactory certification by the VAID (IND).

## 13. TRAINING:

- a) The contractor shall provide factory training in operation, maintenance, calibration and fault identification of the radar system along with modification & up-gradation in application software to 4 persons from IMD for a period of 3 weeks.
- b) During factory training, cost of travel, per diem charges and charges for boarding/lodging for IMD personnel will be borne by IMD, Government of India.
  - c) The training shall also include lectures on the system design, computer hardware/software, operation and such other aspects which are considered essential for optimum utilization of the radar system. The training material will be documented and handed over to the trainees.
  - d) Onsite training in operations and first level fault identification to be provided for a period of five working days at site.

#### 14. DOCUMENTATION:

- a) The contractor shall furnish two copies of the following documentation in well-bound sets/volumes of good print quality for each radar site and two copies of the same to Redar Unit, UAID, New Delhi.
- b) Soft copy of all the manuals should also be provided along with hard copy.
- c) All standard manuals, technical data sheets and other pertinent information of functional, electrical and



machanical modules used in the System shall be included in the manuals.

- d) Interface connectivity document has to be provided for hardware as well as software interfaces.
- e) Detailed documentation of all the proprietary data formats, bit-by-bit information on the header and data patterns should be provided.
- f) Free updates made to firpware, processing software and clarifications should also be supplied with relevant documentation during the period of warranty and CAMC thereof.
- (g) The system functional block diagram shall be laid out so that a user can readily understand and identify the major functions of the system.
- h) The operating instructions shall include routine procedures, safety and emergency procedures as applicable. These instructions shall include switch-on, standby, normal operating procedures and switch off procedures. The sequence of turn-on procedures shall be optimized and shall account for controls at different physical locations. The instructions shall provide assistance to an operator to use the System for optimum performance.
- Sufficient illustrations shall be included to identify and locate all operating controls and indicating devices.
- j) Layout and Schematic Assembly Drawings: Schematic Diagrams of all assemblies, modules shall be provided.
- (k) Parts List: Detailed parts list with part numbers shall be provided.
- Algorithm of Products: The algorithms used in product generation shall be supplied.
- m) It shall be the responsibility of the contractor to provide detailed parts list of modules sourced. List of items imported and incorporated in the system should also be provided separately. Only such items may be used in the system whose technical details are made available by the manufacturer.

## 15. DELIVERY SCHEDULE:

(a) First radar shall be installed, accepted and commissioned within 15 months from the date of signing of contract agreement, Rest of the radar systems shall be delivered, installed and commissioned within 33 months from the date

51

of issue of contract agreement in a phased manner. In this regard the contractor will submit the actual schedule along with time line for execution of installation and commissioning work for each radar.

- Supply of all stores (for first radar) at site within a period of 12 months from issue of contract adreement.
- (ii) Installation of all equipment to test the first radar within two month after supply of equipment
- (iii) Acceptance and commission of first Radar within one month after installation.
- (iv) Supply, installation, acceptance and commissioning of all the remaining radars within a period of 33 months from the issue of contract agreement.
- b) Preliminary Design Review (PDR) will be held after one month from the date of issue of contract agreement wherein the design of hardware & software to be delivered as part of the system will be discussed at the office of UAID, IMD, New Delhi (India).
- c) Critical Design Review (CDR) will be conducted within six months from the date of issue of contract agreement wherein the design along with performance parameters of the sub units will be discussed in detail to ensure that the system achieves the performance parameters to be delivered as per TENDER DOCUMENT.

# Penalty clause/Liquidated damages clause (LD) for delayed stores & Services:

The contractor shall deliver the goods and perform the services (delivery, installation, acceptance and commissioning) under the contract within the time achedule specified by the purchaser in the "Shapter-3/ technical specifications" section and as incorporated in the contract agreement. The LD will be imposed if delivery schedule is not met as per Clause No. 20 of Chapter 2, at the rate of 0.5 % per week of the contract value of each radar. However, the total LD shall not exceed 10% (Ten) percent of the value of delayed goods.

### 17. COMPLIANCE STATEMENT:

a) The contractor shall submit detail para-wise compliance statement as per Annexure--XII format mentioning full details with reference Para, Clause and page no. Of the bid for each parameter along with reasons for compliance/ noncompliance, if any.



- 153/203
- b) The contractor shall also submit the details of references, reports etc. for each compliance giving name of technical menual, chapter number, page number and para and shall provide a copy of referred documents along with the technical bid.
- c) Silence on any para or simply making a statement "complied" without proper justification of reference will be considered as non-compliance.
- d) All the claims with respect to any specification shall be supported by document along with bid document otherwise same may be treated as non-compliance.
- c) Compliance matrix should be filled in at all points of TENDER DOCUMENT individually.
- fi Ail pages should be signed.

### 18. COMPREHENSIVE ANNUAL MAINTENANCE CONTRACT (CAMC) :

- a) The contractor shall quote for CAMC for seven years subsequent to completion of warranty period of three years.
- b) The contractor shall submit year wise lump sum amount of CAMC charges.
- c) The amount charged for CAMC shall not be quoted as percentage of the tender cost / cost of equipment.
- (d) The CAMC charges shall be included for price comparison. The terms & conditions for the CAMC are enclosed at Annexure -V.

#### CHAPTER-4

# PRICE SCHEDULE

## (Financial Bid format)

S. No	Name of	Quantity	Model	Base	Applicable	Unit Price	Total price
-	Item/Store		Number	price	taxes & duties	5+6	(387)
100	101	2430	-	(18)?	5 E N	(7)	(\$1
1820	1.12801.	004300	604 J.	<u></u> \$0₹20	180		
-		Store	Compon	ents (h	ardware 630	ftware etc.)	
			Ser		remotioner som fras		

Total Tender price in figure:

Total Tender price in words:

### NOTE/INSTRUCTION

- The contractor shall use its <u>own letter head</u> for quoting the prices, Document should be signed and stamped on all the pages.
- Price shall be preferred in the format for deliverables for stores 6 services as given at Annexure VI.
- 3. The name of each store/item offered in technical proposal must be sentioned with make a Model including services etc if any. The deliverables list attached with financial bid must be exactly same as per the technical bide.
- 4. Charges, If any, for inlend (within India) Transportation /freight/insurance of stores shall be mentioned. In case not mentioned, it is treated as free of cost.
- 5. If there is a discrepancy between the unit price and total price THE UNIT PRICE shall prevail.

54

## DGM-HQ-24014(11)/1/2021-UAID

#### 17564/2021/UAID DGMHQ

- 6. All applicable taxes must be mentioned against each item. Rate of each applicable tax must be mentioned in price bid. If taxes not mentioned, it is treated that price guoted is inclusive of taxes.
- 7. Costing for each and every items and sub-items which is offered in technical hid shall be given as per details and specifications given in the schedule. Charges for FAT, training, installation, SAT and other services etc. 'are to be mentioned clearly in price bid.
- 8. Price Bid (in .pdf format excluding note/instruction) shall be uploaded on eprocure.gov.in

Signature of contractor

Seal of the contractor

# CHAPTER-5

# OTHER STANDARD FORMS

#### Annexure-I

# CHECKLIST

S. No	Activity	Compliance Yes/ No/ NA	Pages Para No. of the bid Dodument
i.	Is Registration certificate of the Indian Bidder with any state or central government body of India attaches with technical bid?		
2	Is Earnest Money Deposit (END) (Bank Guarantee /FDR) of required amount enclosed 7 (as per Annexure-III)		
3.	Is the EMD submitted by the Bidder other than participating Bidder? If yes, then bid is likely to be rejected.		
4.	Is Registration certificate from NSIC/Government bodies on SSI attached for relaxation of EMD?		
5.	Is validity of EMD kept for 240 days?		
6.	Is the validity of bid as per the TE document?		
Î.	Is the Tender Terms &Conditions Acceptance Form duly filled and signed (1.e. terms and conditions are acceptable)? (as per Annexure+II)		
8.	Is the bld signed? (Tenders is liable to be rejected if not signed)		
9.	Is the clause-by-clause compliance statement for the "List of requirements/ technical specifications "section enclosed? Compliance matrix indicating point wise compliance to all the points of tender document. Each point needs to be complied and single statement for all the points will not be agreed to:		
10.	is the copy of the last purchase order(s) and end user Certificate enclosed?		
11.	Is tender Submitted by an Indian Original Equipment Manufacturer (ICEM)?		
12.	Is tender submitted by a Foreign Original		

Ϊ.	Equipment Manufacturer?	
13.	Whether Back-to-back support agreement with equipment manufacturer and software developer company attached?	
14.	Whether Permanent Account No. of Bldder with proof is provided.	
15.	is sales Aservice tax number/GST with registration certificate attached?	
16.	Name of the Bidder who quoted the price?	
17,	Name of tender currency?	
18,	Name of the bidder with complete address to whom supply order is to be Placed?	
19.	Whether un-priced bid similar to price bid with price hidden as per Chapter-4 is enclosed?	
20.	Whether Signed Integrity Part document as per enclosed format is attached?	
21.	Whether the proforma for performance Statement with documentary proof as per Annexure-VII is enclosed?	

(Name & Signature with date and Bidder/company seal)



Ansexurg-11

# TENDER TERMS & CONDITIONS ACCEPTANCE FORM (All the terms & conditions of tender document are acceptable to tenderer)

#### To,

### The Director General of Meteorology, India Meteorological Department, Lodi Road, New Delhi-110003

Ref: Tender Enguiry (TE) Document No. CPU/ --- dated: -----

1/We, the undersigned have examined the above mentioned TE document, including amendment/corrigendum No. ,....dated.....(if any), the receipt of which is hereby confirmed. We now offer to supply and deliver the goods and services in conformity with your above referred document. If our tender is accepted, we undertake to supply the goods and perform the services (Installation 4 commissioning etc.) as mentioned in tender document with-in the delivery schedule specifies in the "TENDER DOCUMENT- Chapter-3/ technical specifications".

1/We further confirm that, if supply / purchase order is placed to our firm, we shall provide performance security of required amount in an acceptable form for due performance of the contract within the scheduled time.

1/ We agree to keep our tender valid for acceptance as required in tender document or for subsequently extended period, if any, agreed to by us.

I/ We also accordingly confirm to abide by this tender up to the aforesaid period and this tender may be accepted any time before the expiry of the aforesaid period.

I/We further confirm that, until a formal contract is executed, this tender read with your written acceptance thereof within the aforesaid period shall constitute a binding contract between us.

1/ We further understand that you are not bound to accept the lowest or any tender you may receive against your abovereferred tender enquiry. (Signature with date and seal of the company)

I/We are not involved in any litigation that may have an impact of affecting or compromising the delivery of services as required under this assignment.

夥

I/We confirm that we have not been deregistered/banned/blacklisted by any Central/ State Government/ agency of Central/ State Government of India or any other country in the world/ Public Sector Undertaking/ any Regulatory Authority in India or any other country in the world for any kind of fraudulent activities on the date of submission of Bids.

I/ We confirm that we fully accept and agree to all the terms and conditions specified in above mentioned TE document, including emendment/ corrigendum etc. if any.

[Name and designation]

Duly authorised to sign tender for and on behalf of tenderer

#### Note\*:

- Bidder/company shall use their own printed letter head for issuing this certificate.
- 2, Acceptance shall be unconditional.

Annexure - III

#### MODEL BANK GUARANTEE FORMAT FOR FURNISHING EMD

(Format only)

Whereas

(hereinafter called the "tenderer")

.. are bound into ...... (hereinafter called the "Furchaser)

in the sum of finite first structure of the made to the said Furchaser, for which payment will and truly to be made to the said Furchaser, the Bank binds itself, its successors and assigns by these presents. Sealed with the Common Seal of the said Bank this day

THE CONDITIONS OF THIS OBLIGATION ARE:

(1) If the tenderer withdraws or amenda, impairs or derogates from the tender in any respect within the period of validity of this tender.

(2) If the tenderer having been notified of the acceptance of his tender by IMD during the period of its validity:-

- If the tenderer fails to furnish the Performance Security for the due performance of the contract.
  - · falls or refused to accept/execute the contract.

We undertake to pay the "Director General of Meteorology, India Meteorological Department", up to above amount upon receipt of its first written demand, without IND Having to substantiate demand, provided that is its demand IMD will note that the amount claimed by it is due to owing to the occurrence of one or both the two conditions, specifying the occurred condition / conditions.

This guarantee will remain in force up to and including 160 days or after the finalisation of tender any demand in respect thereof should reach the Bank not later than the above date. Bank Quarantee issued with the tender enquiry reference No.

#### (Signature of the authorized officer of the Bank)

Name and designation of the officer

Seal, name & address of the Bank and address of the Branch

/ 60

Annexure - IV

#### BANK GUARANTEE MODEL FORMAT FOR PERFORMANCE SECURITY

To, The President of India

Through :-

Director General of Meteorology, India Meteorological Department, Lodi Road, New Delhi-110008

WHEREAS (Name and address of contractor) (Hereinafter called "contractor") has undertaken, in pursuance of contract no dated to supply (description of goods and services) (herein after called "the contract").

AND WHEREAS it has been stipulated by you in the said contract that contractor shall furnish you with a bank guarantee by a Nationalized bank recognized by you for the sam specified therein as security for compliance with its obligations in accordance with the contract;

AND WHEREAS we have agreed to give contractor such a bank guarantee;

NGW TREREFORE we hereby contractor that we are quarantons and responsible to you, on behalf of contractor, up to a total of. (Amount of the quarantee in words and figures), and we undertake to pay you, upon your first written demand declaring contractor to be in default under the contract and without cavil or argument, any sum or sums within the limits of (amount of guarantee) as aforesaid, without your needing to prove or to show grounds or reasons for your demand or the sum specified therein.

We hereby waive the necessity of your demanding the said debt from contractor before presenting us with the domand. We further agree that no change or addition to or other modification of the terms of the contract to be performed there under or of any of the contract documents which may be made between you and contractor shall in any way release us from any liability under this guarantee and we hereby waive



# DGM-HQ-24014(11)/1/2021-UAID

notice of any such change, addition or modification.

This guarantee shall be valid up to and including the \_\_\_\_\_ day of \_\_\_\_\_, 20\_\_\_\_

(Signature with date of the authorized officer of the Bank)

Name and designation of the officer

Seal, name & address of the Bank and address of the Branch



#### Annexure-V

# Terms & Conditions of Comprehensive Annual Maintenance Contract (CAMC) of X-Band Dual Polarized Doppler Weather Radars

- The CAMC includes Control Center and Radar Site Material & Services inclusive of all Computer peripherals, Frinters, Radar modules, spares, components, cables, connectors atc and radar related materials like UPS, DG, Radome, Towar, etc. and the removed/replaced defective material becomes the property of "Successful contractor".
- The CAMC amount cannot be less than 5% (for entire CAMC period per year) of the total cost of the DNR including all sub systems.
- The CAME classe will be applicable for control center and individual radar sites separately.
- 4. The CAMC will commence immediately after the explicit of the warranty period. The comprehensive service includes preventive and corrective maintenance and free replacement of all the defective parts/devices. The company should submit a detailed CAMC plan including preventive maintenance schedule.
- 5. The Contractor shall supply the details of its call conters meant for booking the complaints along with the contact numbers like mobile nos., phone hos., mail address and names atc of its service engineers.
- The radar shall be decommissioned for a period of two weeks only for annual preventive maintenance and upkeep in a cyclic mode.
- The Contractor's engineers attending to the system are required to make all entries of their work done and corrective measures taken by them with their signatures in the log book kept with the Radar.
- 8: Overall uptime of the system shall be at least 95%. If there is a failure of the system for more than the criteria stipulated then the CAMC amount of 0.5% per day, for days it is down will be deducted, subjective to an upper celling of 10% of CAMC charges for that quarter. If the failure duration extends beyond one month then the contract may be terminated and cost of its repair from alternate source will be recovered from the Contractor and performance security may be forfeited. Maximum two weeks shutdown for annual maintenance shall not come

63

under the clause. Radar down time due to external factors and severe natural calamity beyond human control shall exempt the driteria.

- Successful Contractor shall ensure 95% uptime by supportive manpower if found necessary.
- Date of commencement of Annual Maintenance Period of the individual radars shall be fixed by IND.
- The mode of payment will be quarterly and will be made after end of each quarter on the basis of satisfactory performance certificate from user.
- "Successful contractor" will assist IND for regular backups of all the software. The Contractor is also required to restore the existing Software from the Backups whenever required.
- 13. Contractor will also be responsible for configuring the networking components.
- 14. CAMC contract will be sighed for <u>seven years</u>. If required, contract may be extended by IMD, However, IMD reserves the right to terminate the contract at any time by giving three months' notice, if the performance of the system or the services rendered by the contractor is not found satisfactory.
- The contractor has to submit an undertaking that it will not use IND data for any convercial purpose.
- This contract shall be governed in all respects by Indian Laws.

(Signature of the authorized officer of the Successful contractor)

Seal, name & address of the Successful contractor

Name and designation of the officer

- 64

#### Anaexure- VI

# FORMAT FOR DELIVERABLES FOR SUPPLY OF Eight (08) NOS. SSPA BASED X-BAND DUAL POLARIZED DOPPLER WEATHER RADARS

S. No	Items Description	Qty.	Model & country of origin	Cost Per Unit	Taxes	Tota 1 cost
	X-Band dual polarized SSPA based Doppler Weather Radar system including all units/sub units and accessories as follows:	8 Sets				
1	Trensmitter	8				
2	Receiver	8		1		1
3	Antenna control unit and Radar control unit	8				
iii.	Radar signal processor	8				
15	Radome, Antenna 6 Anterna Pedastal	8				
10	Peripherals at 8 sites as per detail at 2.40. Page No.36	8				
ų	Radar Application and Operating Software	8				
8	Peripherals as per detail at 2.40, Page No.36 for one central server at Delhi.	1				
9	Server with WebGIS at 8 sites 6 1 at control center	<u>.</u>				
10	Equipment Shelter	9				1
14	Tower	8				
12	Acceptance testing (Site)	8 <b>8</b> 8				
13	Installation	8				
14	Services	8				
15	Products (Software)	8				
16	Any other unit/subunits/ item not listed above but required for functioning of	÷				

14 65

## 17564/2021/UAID DGMHQ

# DGM-HQ-24014(11)/1/2021-UAID

	DWR shall also be included	
1.7	Installation material	3
50/1/		
18	Documentation both hard copy and soft copy	18
19	Communication hardware/ software for data transfer to control center location.	£
20	Training to IMD personnel at each site after completion of installation / commissioning for five working days. Note: Expenses for trainees such as airfare , lodging and per diem to be borne by IMD	9 1
21	Training to IND personnel at factory for three weeks. Note: Expenses for trainees such as sinfare , lodging and per diem to be borne by IMD	
22	7 years (Year - wise) comprehensive Annual Maintenance Contract (CAMC) (for all radar sites and central servers) after the expiry of 3 years warranty period	
	1 <sup>st</sup> Year CAMC 2 <sup>nd</sup> Year CAMC 3 <sup>sd</sup> Year CAMC 8 <sup>th</sup> Year CAMC 6 <sup>th</sup> Year CAMC 5 <sup>th</sup> Year CAMC 7 <sup>th</sup> Year CAMC	
23	Towers for installation inclusive of all civil works	8
24	Two UPSs each of minimum 10 RVA departy or as per system requirement.	8
25	Enclosure with appropriate cooling (Pt. 2.44, Page No. 38)	8
26	Diesel cenarator of 15 804	8

66

(minimim)	02	a s	plez	1:M8			1	
system req	utre	menta	8					

## \*Note:

- Since the date of installation and commissioning of each individual Radar may be different, the rate for deciding cost of CAMC per site shall be decided on pro rate basis based on overall cost of CAMC per month divided by the number of Radars.
- No extra cost will be paid for initial three years warranty.
- All the above items are to be supplied in quantities shown above. However, if a particular item is combined with another item the fact may be so stated against that item without dropping it.
- If a particular item is not used in the radar system it may be so stated against that item.
- If an item equivalent to the listed items is used in the radar, details of same may be stated against that item.
- Successful Contractor shall also include any other recommended spares (one each) specific to their radar system and identified as critical item. No additional cost shall be paid for such extra item.

(Signature of the authorized officer of the contractor)

Seal, name & address of the contractor

Name and designation of the officer
17564/2021/UAID DGMHQ

168/203

Annexure - VII

#### PROFORMA FOR PERFORMANCE STATEMENT

Bid No.

Name of the successful contractor

Order placed by (Full address of Organisation)	Order No. and date	Description and quantity of ordered equipment	Value of order	Date of completion of delivery as per contract actual	Remarks including reason for late delivery, if any	Has the equipment been satiofactorily functioning?

Signature of the authorized officer of the Successful Contractor

Name and designation of the officer

Seal, name & address of the Bidding Contractor

68

Annexure- VIII

## List of tentative locations for installation of Eight (08) X-Band Doppler Weather Radars

S.No	Name of the stations.
1	Guwahati
7.7	Imphal
100	Silcher
4	Alzwal
5	Dimapur
6	Rohima
12	Jorhat
8	Passighat



Annexure- IX

#### INTEGRITY PACT

#### Between

India Meteorological Department, Ministry of Earth Sciences. Govt of India hereinafter referred to as "The Principal", and hereinafter referred to as "The Bidder/ Contractor".

#### Preamble

The Frincipal intends to award, under laid down organizational procedures, contract/s for..... The Frincipal values full compliance with all relevant laws of the land, rules, regulations, economic use of resources and of fairness / transparency in its relations with its Bidder(s) and / or Contractor(s).

In order to achieve these goals, the Principal will appoint Independent External Manitors (IZMs) who will monitor the Leader process and the execution of the contract for compliance with the principles mentioned above.

#### Section 1- Commitments of the Principal

(1) The Principal commits itself to take all measures necessary to prevent corruption and to observe the following principles:

a. No employee of the Principal, personally or through family members, will in

connection with the tender for, or the execution of a contract, demand, take a promise for or accept, for self or third person, any material or immaterial benefit which the person is not legally entitled to.

b. The Principal will, during the tender process treat all Bidder(s) with equity and reason. The Principal will in particular, before and during the tender process, provide to all Bidder(s) the same information and will not provide to any Bidder(s) confidential / additional information through which the Bidder(s) could obtain an advantage in relation to the tender process or the contract execution.

G. The Principal will exclude from the process all known prejudiced persons.

(2) If the Principal obtains information on the conduct of any of its employees which is a criminal offence under the IPD/PC

70

Act, or if there be a substantive suspicion in this regard, the Principal will inform the Chief Vigilance Officer and in addition can initiate disciplinary actions.

#### Section 2 - Commitments of the Bidder(s) / Contractor(s)

(1) The Bidder(s) / Contractor(s) commit themselves to take all measures necessary to prevent corruption. The Bidder(s) / Contractor(s) commit themselves to observe the following principles during participation in the tender process and during the contract execution.

a. The Bidder(s)/ Contractor(s) will not, directly or through any other person or firm, offer, promise or give to any of the Principal's employees involved in the tender process or the execution of the contract or to any third person any material or other benefit which he/she is not legally entitled to, in order to obtain in exchange any advantage of any kind whatsoever during the tender process or during the execution of the contract.

b. The Bidder(s)/ Contractor(s) will not enter with other Bidders into any undisclosed agreement or understanding, whether formal or informal. This applies in particular to prices, specifications, certifications, subsidiary contracts, subsission or non-submission of bids or any other actions to restrict competitiveness or to introduce cartelisation in the bidding process.

c. The Bidder(s)/ Contractor(s) will not commit any offence under the relevant IPC/PC Act; further the Bidder(s)/ Contractor(s) will not use improperly, for purposes of competition or personal gain, or pass on to others, any information or document provided by the Principal as part of the business relationship, regarding plans, technical proposals and business details, including information contained or transmitted electronically.

d. The Bidder(s)/Contractors(s) of foreign origin shell disclose the hame and address of the Agents/representatives in India, if any, similarly the Bidder(s)/Contractors(s) of Iodian Nationality shall furnish the name and address of the foreign principals, if any. Further details as mentioned in the "Guidelines on Indian Agents of Foreign Suppliers" shall be disclosed by the Bidder(s)/Contractor(s). Further, as mentioned in the Guidelines all the payments made to the Indian agent/representative have to be in Indian Rupees only. Copy of the "Guidelines on Indian Agents of Foreign Suppliers" is placed at (page nos, 6-7).

e. The Bidder(s)/ Contractor(s) will, when presenting their bid, disclose any and all payments made, is committed to or intends to make to agents, brokers or any other intermediaries in connection with the award of the contract.

n n

#### 17564/2021/UAID DGMHQ

172/203

f. Bidder(s) / Contractor(s) who have signed the Integrity Pact shall not approach the Courts while representing the matter to TEMs and shall wait for their decision in the matter,

12) The Bidder(s)/ Contractor(s) will not instigate third persons to commit offences outlined above or be an accessory to such offences.

# Section 3 - Disqualification from tender process and exclusion from future contracts

If the Bidder(s)/Contractor(s), before award or during execution has committed a transgression through a violation of Section 2, above or in any other form such as to put their reliability or credibility in question, the Principal is entitled to disgualify the Bidder(s)/Contractor(s) from the tender process or take action as per the procedure mentioned in the "Guidelines on Banning of business dealings". Copy of the "Guidelines on Banning of business dealings" is placed at (page nms, 8-17).

#### Section 4 - Compensation for Damages

(1) If the Brindipal has disgualified the Bidder(s) from the tender process prior to the award according to Section 3, the Principal is entitled to demand and redover the damages equivalent to Earnest Money Deposit/ Bid Security.

(2) If the Principal has terminated the contract according to Section 3, or if the Principal is entitled to terminate the contract according to Section 3, the Principal shall be entitled to demand and recover from the Contractor liquidated damages of the Contract value or the amount equivalent to Performance Bank Guarantee.

#### Section 5 - Previous transgression

(1) The Bidder declares that no previous transgressions occurred in the last three years with any other Company in any country conferming to the anti-corruption approach or with any Public Sector Enterprise in India that could justify his exclusion from the tender process.

(2) If the Bidder makes incorrect statement on this subject, he can be disqualified from the tender process or action can be taken as per the procedure mentioned in "Guidelines on Barming of business dealings".

Section 6 - Equal treatment of all Bidders / Contractors / Subcontractors

(1) In case of Sub-contracting, the Principal Contractor shall take the responsibility of the adoption of Integrity Pact by

the Sub-contractor.

(2) The Principal will enter into agreements with identical conditions as this one with all Bidders and Contractors.

(3) The Principal will disqualify from the tender process all bidders who do not sign this Pact or violate its provisions.

# Section 7 - Criminal charges against violating Bidder(s) / Contractor(s) / Subcontractor(s)

If the Principal obtains knowledge of conduct of a Bidder, Contractor or Subcontractor, or of an employee of a representative or an associate of a Bidder, Contractor or Subcontractor which constitutes corruption, or if the Principal has substantive suspicion in this regard, the Brincipal will inform the same to the Chief Vigilance Officer.

#### Section 8 - Independent External Monitor

(1) The Principal appoints following competent and credible Independent External

Monitor for this Fact after approval by Central Vigilance Commission. The task of the Monitor is to review independently and objectively, whether and to what extent the parties comply with the obligations under this agreement.

1. Dr. S. K. Sarkar, IAS(Retd.), B-104, Nayantara Aprt., Plot 8 B, Sector= 07, Dwaska, New Delhi= 10075 E Mail:sksarkarl 9796cmail.com; Mobile No. 981 1 1 49324

2. Shri Rakesh Goyal, IRSE(Retd.)

2094, Joy Apartment,

Sector 2, Dwarka,

De1b1 -"1 10075

E Mail: goval125980mail.com ; Mobile No. 9717644264

(2) The Monitor is not subject to instructions by the representatives of the parties and performs his/her functions neutrally and independently. The Monitor would have access to all Contract documents, whenever required. It will be obligatory for him / her to treat the information and documents of the Bidders / Contractors as Confidential. He/ she reports to the Director General of Mateorology, India Mateorological Department, New Delhis.

174/203

(1) The Bidder(s)/ Contractor(s) accepts that the Monitor has the right to access without restriction to all Project documentation of the Principal including that provided by the Contractor, The Contractor will also grant the Monitor, upon his/her request and demonstration of a valid interest, unrestricted and unconditional access to their project documentation. The same is applicable to Sub-contractors.

(4) The Monitor is under contractual obligation to treat the information and documents of the Bidder(s)/ Contractor(s)/ Sub-contractor(s) with confidentiality. The Monitor has also signed declarations on 'Non-Disclosure of Confidential Information and of 'Absence of Conflict of Interest. In case of any conflict of interest arising at a later date, the IEM shall inform to the Director General of Meteorology, India Meteorological Department, New Delhi and recuse himself / herself from that case.

(5) The Principal will provide to the Monitor sufficient information about all meetings among the parties related to the Project provided such meetings could have an impact on the contractual relations between the Principal and the Contractor. The parties offer to the Monitor the option to participate in such meetings.

(6) As soon as the Monitor notices, or believes to notice, a violation of this agreement, he/she will so inform the Management of the Principal and request the Management to discontinue or take corrective action, or to take other relevant action. The monitor can in this regard submit nonbinding recommendations, Beyond this, the Monitor has no right to demand from the parties that they act in a specific manner, refrain from action or tolerate action.

(7) The Monitor will submit a written report to the Director General of Meteorology, India Meteorological Department, New Delhi within 8 to 10 weeks from the date of reference or intimation to him by the Principal and, should the occasion arise, submit proposals for correcting problematic situations.

(8) If the Monitor has reported to the the Director General of Meteorology, India Meteorological Department, New Delhi , a substantiated suspicion of an offence under relevant IPC/ PC Act, and the the Director General of Meteorology, India Meteorological Department, New Delhi has not, Within the reasonable time taken visible action to proceed against such offence or reported it to the Chief Vigilance Officer, the Monitor may also transmit this information directly to the Central Vigilance Commissioner.



111

(9) The word 'Monitor would include both singular and plural.

#### Section 9 - Fact Duration

This Fact begins when both parties have legally signed it. It expires for the Contractor 12 months after the last payment under the contract, and for all other Bidders 6 months after: the contract has been ewarded. Any violation of the same would entail disqualification of the biddens and exclusion from future business dealings.

If any claim is made / lodged during this time, the same shall be binding and continue to be valid despite the lapse of this. pact as specified above, unless it is discharged / determined by the Director General of Meteorology, India Meteorological Department, New Delhi .

#### Section 10 - Other provisions

(1) This agreement is subject to Indian Law. Place of performance and jurisdiction is the Registered Office of the Principal, i.e. New Delhi.

(2) Changes and supplements as well as termination notices. need to be made in writing, Side agreements have not been made.

(3) If the Contractor is a partnership or a consertion, this agreement must be signed by all partners or consortium members,

(4) Should one or several provisions of this agreement turn out to be invalid, the remainder of this agreement remains valid. In this case, the parties will strive to come to an agreement to their original intentions.

(5) Issues like Warranty / Guarantee etc. shall be outside the purview of IEMs.

(6) In the event of any contradiction between the Integrity Pact and its Annexure, the Clause in the Integrity Pact will prevail.

(For & On behalf of the Principal)

(For & On behalf of Bidder/ Contractor)

(Office Seal)

(Office Seal)

Date ----

P1208 -----

## DGM-HQ-24014(11)/1/2021-UAID

176/203

Witness I:

(Nace 5 Address)

Witness 2:

(Name 5: Address)



75

Annexuze-X

## PROFORMA FOR CERTIFICATE FROM THE USER INDICATING SUCCESSFUL OPERATION OF RADAR

#### TO WHOMSOEVER IT MAY CONCERN

This is to certify that the Doppler Weather Radar with associated subsystems and peripherals supplied by to \_\_\_\_\_\_ for \_\_\_\_\_ to \_\_\_\_\_ vide \_\_\_\_\_\_ Vide \_\_\_\_\_\_ Vide \_\_\_\_\_\_ Vide \_\_\_\_\_\_ Vide \_\_\_\_\_\_ (copy enclosed) installed and commissioned on \_\_\_\_\_\_\_

The said radar is under continuous operation since \_\_\_\_\_\_ and are providing satisfactory results.

Signature of authorized signatory

Name of authorized signatory

Complete office address

With office seal and date

Annexuze-XI

#### Non-Blacklisting declaration

#### (Sample Format only)

10: \*

Dates

(Consignee Name and address)

Bear Sir,

- a) We are not involved in any major litigation that may have an impact of affecting or compromising the delivery of services as required under this assignment.
- b) We are not blacklisted by any Central/ State Government/ agency of Central/ State Government of India or any other country in the World/ Public Sector Undertaking/ any Regulatory Authorities in India or any other country in the World for any kind of fraudulent activities.

Sincerely,

BIDDERS NAME!

Name Title Signature



## Annexure - XII

## Compliance statement

Schedule of requirements, specif allied technical details.	fications &	C or NC with Chapter, Clause, and Page No. of the Bid Document
Special Conditions of Contra-	ct (SCC)	
Supplier shall submit their bids for numbers of X-Band Dual Polarization Do Radars with Solid State Power Amp transmitters.	r Eight (08) ppler Weather liffer based	
1. GENERAL REQUIREMENT:		
The specifications described herein refer to 9500 MHz! Dual Polarized SSPA based Doppler including all peripherals, hereafter referre System". The System shall be capable of a estimating meteorological parameters of se phenomena that cause widespread damage ( property.	X-Band (9300- Weather Radar d to as "The letecting and vere weather to life and	
All the DWR systems to have following la the art facilities for smooth operation radar system and its accessories:	test state of a of complete	
<ol> <li>Diesel generator of minimum 15 KWA capacity required for continuous operat DWR system including cooling system, minimum 100 L capacity fuel tank. Die shall have automated switching on and o the event of normal electricity resumption.</li> </ol>	or suitable ion of entire along with sel generator if feature in failure and	
ii. Two online DPSs, in redundant mode a minimum capacity of 10KVA each or suit required for continuous operation of system, along with separate battery bar should have at least 30 minutes cover should be capable of taking the full load	nd each with able capacity entire DWR tks. Each UPS back-up and d of rader.	
III, NTP clock based on GFS for system synchronisation of the radar and t computers in the radar network.	clock time he connected	

y. The sin Hoi via The via Lat this via Lat this use ix The sys and sys sys sys and sys sys sys and sys sys and sys sys and sys and sys sys and sys sys and y and sys an sys an sys an sys an sys an sys an sys an sys an sys sys an sys an sy	<pre>e system will have dual polarization capability by multaneous transmission and receive in both linear rizontal and Vertical polarizations. e System shall have user selectable Single larization and Dual polarization mode of operation. test state of art computer system shall be used for e generation of data and its processing. he entire operation of the System shall be fully mputer controlled and remotely manageable. re tentative locations for installation of the stems are mentioned in Annexure-VIII istallation of radar system will be on steal tower nucture fabricated using hot dipped galvanized sel, at site. The standard of the steel and estemss shall be certified for use in saline storment specified in Indian standard vecification manual and specified explicitly. The secification shall meet minimum IS2062:2011 5250 ade-C Steel for Channels and plates and IS1501:2014 IS10748:2004 SST 310 grade steel for hollow pipes, 51367 Grade 8.8 for fasteners from reputed unifacturers and their details also shall be domitted. is tower structure shall be with height of 20m. or evaluation of tender, cost of the tower will be</pre>	
via Lat via Lat this ulti The use ix The sys and stan ent sys fan ent sys ent sys ent sys fan ent sys sys sys sys sys sys sys sys sys sy	<pre>ne System shall have deer selectable Single larization and Dual polarization mode of operation; test state of art computer system shall be used for re generation of data and its processing. ne entire operation of the System shall be fully mputer controlled and remotely manageable. te tentative locations for installation of the stams are mentioned in Annexure-VIII istallation of radar system will be on steel tower ructure fabricated using hot dipped galvanized cel, at site. The standard of the steel and isteners shall be certified for use in saine wirnoment specified in Indian standard mecification nanual and specified explicitly. The secification shall neet minimum IS2062:2011 E250 rade-C Steel for Channels and plates and IS161:2014 IS10748:2004 VST 310 grade steel for hollow pipes. S1367 Grade 8.8 for fasteners from reputed inificationes and their details also shall be dmitted. is tower structure shall be with height of 20m. if evaluation of tender, cost of the tower will be sterification of tender.</pre>	
via po via Lat thi dili The use ix The sys a ix Sta sys sys a in sta spe in spe spe in spe in spe in spe in spe in spe in spe in spe in spe in spe in spe sp in spe in spe s spe in s spe s spe s s s s s s s s s s s s s s	<pre>iterization and Dual polarization mode of operation. test state of art computer system shall be used for e generation of data and its processing. he entire operation of the System shall be fully mputer controlled and remotely manageable. te tentative locations for installation of the stems are mentioned in Annexure-VIII istallation of radar system will be on steal tower ructure fabricated using hot dipped galvanized sel, at site. The standard of the steel and isteners shall be certified for use in saline stironment specified in Indian standard vecification manual and specified explicitly. The secification shall meet minimum IS2060:2011 E250 ade-C Steel for Channels and plates and IS1161:2014 IS10748:2004 VST 310 grade steel for hollow pipes. S1367 Grade 8.8 for fasteners from reputed inifacturers and their details also shall be dmitted. is tower structure shall be with height of 20m. if evaluation of tender, cost of the tower will be presented of the steel for hollow pipes.</pre>	
<pre>viii List this this cliff The cost ix The sys ix State sys sys sys sys sys sys sys sys sys sy</pre>	The generation of data and its processing. The entire operation of the System shall be fully mputer controlled and remotely manageable. The tentative locations for installation of the stems are mentioned in Annexure-VIII istallation of radar system will be on steal tower ructure fabricated using hot dipped galvanized cel, at site. The standard of the steel and steners shall be certified for use in saline stironment specified in Indian standard pecification shall meet minimum IS2060:2011 E250 rade-C Steel for Channels and plates and IS1161:2014 IS10748:2004 VST 310 grade steel for hollow pipes. S1367 Grade 8.8 for fasteners from reputed mufacturers and their details also shall be abmitted. The tower structure shall be with height of 20m.	
diii The USN 1× The Sys 2× Sti 55% 181 55% 181 55% 181 181 181 181 181 181 181 181 181 18	the entire operation of the System shall be fully mputer controlled and remotely manageable. The tentative locations for installation of the stems are mentioned in Annexure-VIII istallation of radar system will be on steal tower nucture fabricated using hot dipped galvanized cel, at site. The standard of the steel and steners shall be certified for use in saline vironment specified in Indian standard pecification manual and specified explicitly. The secification shall meet minimum IS2060:2011 E250 rade-C Steel for Channels and plates and IS1161:2014 IS10/48:2004 VST 310 grade steel for hollow pipes, S1367 Grade 8.8 for fasteners from reputed andiscturers and their details also shall be donitted. The tower structure shall be with height of 20m. The revaluation of tender, cost of the tower will be	
IX The sys X Sti fat on Sp Sp Gn Sp Gn K TS Sat Sub Sti Sub Sti Sub Sti Sub Sti Sub Sti Sub Sti Sub Sti Sub Sti Sub Sti Sub Sti Sub Sti Sub Sp Sp Sp Sp Sp Sp Sp Sp Sp Sp Sp Sp Sp	the tentative locations for installation of the (stems are mentioned in Annexure-VIII) istallation of radar system will be on steal tower ructure fabricated using hot dipped galvanized cel, at site. The standard of the steel and isteners shall be certified for use is saline (vironment specified in Indian standard pecification manual and specified explicitly. The pecification shall meet minimum IS2562:2011 £250 rade-C Steel for Channels and plates and IS1161:2014 IS10748:2004 EST 310 grade steel for hollow pipes. S1367 Grade 8.8 for fasteners from reputed inifacturers and their details also shall be dmitted. We tower structure shall be with height of 20m. If evaluation of tender, cost of the tower will be	
xi The sty factor sty factor sty sty sty factor sty factor sty factor sty factor sty factor sty factor sty sty factor sty factor sty sty sty factor sty sty sty factor sty sty sty factor sty sty sty factor sty sty sty sty sty sty sty sty sty sty	istaliation of radar system will be on steal tower ructure fabricated using hot dipped galvanized cel, at site. The standard of the steel and isteners shall be certified for use in saline evironment specified in Indian standard pecification manual and specified explicitly. The becification shall meet minimum IS2060:2011 E250 rade-C Steel for Channels and plates and IS161:2014 IS10748:2004 VST 310 grade steel for hollow pipes. S1367 Grade 8.8 for fasteners from reputed inifacturers and their details also shall be abmitted.	
sti The con dis App les siv The op	tower structure shall be with height of 20m. In evaluation of tender, cost of the tower will be	L
sii Fo co dis App le siv Th op	ir evaluation of tender, cost of the tower will be	
ais. App le siv The	msidered.	
sty The	propriate cemented ceinforced concrete base, eveling arrangement.	
<b>て</b> 泊。 1955	te guoted software should be in use in any perational weather services in the world to fulfil te functional requirements along with capabilities wich have been specified elsewhere in detail.	
av At of shi pro Win	I the time of supply of the stores, the latest state art computer system and latest version of software hall be provided for the generation of data and it's pocessing, with CEM Licensed Version of Linux / indows Operating System.	
xvi.Al ∈n	I equipment shall be of industry standard so as to able easy up-gradation and maintenance.	d
cell Mar har pri her	mufacturer shall submit the full details of the undware, including model numbers and the software oposed to be employed for meeting the requirements given unein.	

## DGM-HQ-24014(11)/1/2021-UAID

201251	Central server at Delhi for processing the radar data from all eight radars to be provided.	
*2×	Facility for radar data analysis and products generation at each of the sites inclusive of automatic dissemination of warnings and alerts are to be provided by the bidder.	
××.	Display of Sata such as reflectivity, rainfall rate, horizontal winds at designated height, warnings etc., to be overlaid on GIS map.	
883.	Web access to GIS based radar data display to be provided using web browsers such as Microsoft Internet Explorer, Firefox, Chrome etc.	
××(1.	GIS based display should be accessible over the network through VPN or internet.	
30(111	The contractor has to clearly specify the way of achieving the sensitivity & detection capability (with ref. to OVERALL SYSTEM REQUIREMENTS) with supportive documents of claim and appropriate calculations for SSPA transmitters. The calculations for achieving the required operational characteristics such as scanning capabilities, maximum range, maximum velocity, sensitivity and clutter suppression have to be provided. Confirmation with supporting images, test printoets etc., are to be previded.	
saiy.	Lightning protection is to be provided for ensuring safety of the system and all tower mounted elements by the way of grounding cable through ground ber or other best suited mechanism.	
XXV.	The supplied DG Set, CPS etc., should have AMC service support facility in India.	
XHVI.	IND will take possession after appropriate test and evaluation meeting the specifications and accept the radar system after commissioning.	
xxvi	It is the responsibility of the hidder to bear all the expenditure to operate the radar including manpower requirements, security and all radar peripherals till successful acceptance and commissioning.	

M

## DGM-HQ-24014(11)/1/2021-UAID

182/203
---------

es#111.	Transportation from the factory to the site will be the responsibility of the vendor.
8812)	The entire work of installation and commissioning of the radar has to be carried out by the contractor.
XXX.	The network link between the systems and central server will be provided by IMD; Successful contractor shall suggest suitable bandwidth for real time system control, monitoring and near real-time receipt of data at central locations for generating composito images and products of all the radars.
	The price blds of technically qualified Bidders shall be spened for evaluation on a date notified after evaluation of the techno commercial bid.

## 2. OVERALL SYSTEM REQUIREMENTS

## Technical Specification

		(A).General
2.1	Range of observation	100 Em (Reflectivity) 100 Em (Velocity, Spectrum Width)
2.2	Range resolution	150 m or better
2.3	Max. Unambiguous Range	100km or better consistent with PRF 5. 2 <sup>mi</sup> trip echo.
2.4	Unambiguous Velocity	30 m/s or better with ambiguity resolver
2.5	Detection capability	13 dBZ or better at 100 km range.
2.6	VSWR	1, 25:1
2.7	Scan Time	10 elevation volume scan with all base moments acquired in Sminutes or better.
		(B). Transmitter
2.8	Transmitter Type	Tunable Power Solid State Power Amplifier based system
2.9	Frequency Range	9.3 GHz - 3.4 GHz
2.10	Transmitted power	Required to meet 13 dBz at 100 Km as per Point No.2.5.
2,11	Pulse repetition frequency	Th meet Range and Velocity requirement as per Points No. 2.3 42.4
2,12	Pulse width	SSPA based system to meet the average power at variable pulse of transmissions at different carrier

82

		frequencies as per 2.5	
2.13	Transmitter Polarization	STAR	
2.14	Modulator	Solid state	
2.15	VSWR	1.26:1	
<u>.</u>	(C)	. Antenna, Radome Tower	
2.16	Antenna	Parabollo Dish Antenna	
2.17	Side lobe	260B down from the Main labe to 12" and beyond 12" better than 30dB.	
2.18	Beam width	1° or hetter	
2.19	Azimuth steering	360° with 10.05" accuracy and 0+5 rpm	
2.20	Vertical Steering	-2° to +92° or better with ±0.05° accuracy	
2.21	Polarization	Serigontal, Vertical and STAR mode	
2.22	Scanning rates	Up to 6 rpm	
2.23	Scan strategy	Provision for automatic changeover between different scan strategies shall be possible.	
2.24	Radome	<ol> <li>Type: Rigid spherical in shape (curved panels) Installed on galvanized steel Tower covering antenna dish and pedestal, with adequate space for maintenance personnel to enter and work.</li> </ol>	
23220	1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.	one way.	
2.25	Wind load	condition up to 250 km/hr	
2.26	Lightning Protection	Lightening rod with dual ground wires.	
2.27	Obstruction lights	Twin Light System with solar powered Sauto switch with long life lamps. Roof hatch for maintenance of obstruction lights and entry from bottom; suitable portable ladder for the purpose of maintenance.	
2.28	Tower height	20m/	
	R A	(D). Receiver	
2.29	Тура	Multichannel Digital receiver for Dual Polarization (RAV), STAR mode operation	
2.30	Noise figure	3 dB or hetter	
2022/222	Linear	95d8 or better	

## DGM-HQ-24014(11)/1/2021-UAID

184/203

2.32	Minimum Discernable Signal	FRANCHON OF FREES
	(E)	. Radar Signal Processor
2.33	Doppler processing	Pulse Pair and FST selectable
2.34	Clutter suppression	Clutter Elimination for 245 dB. The system shall have provision for identifying and filtering non- meteorological echoes such as anomalous propagation echoes. Sea clutters, bird/insects, chaffs, etc. based on polarimetric measurements.
2.35	Range Side lobe	Better than 35dB
2.36	Parameters to be measured and displayed	<pre>(g) Reflectivity (Z<sub>k</sub>) • Dynamic range : -30 to 65 dBZ • Resolution : 0.1 dB Accuracy : \$1dB @ SNR&gt;10dB ; r&lt;100Km; Δr&lt;1Km (h) Radial velocity (V<sub>a</sub>) • Max : t30m/s • Resolution : 0.1 m/s Accuracy :\$1 m/s @SNR &gt;10dB; σ,=4 m/s ; r= 100 Km; Δr&lt;250m (i) Spectrum Width (σ<sub>k</sub>) • Max : r15m/s • Resolution: 0.1 m/s Accuracy:\$2 m/s @SNR &gt;10dB; σ,=4 m/s ; r= 100 Km; Δr&lt;250m (j) Differential reflectivity(Z<sub>0R</sub>) • Dynamic range : -5 to 8 dB2 • Resolution : 0.1 Db Accuracy :\$ 0.2dB @ SNR&gt;10dB ; r&lt;100Km; Δr&lt;1Km (k) Differential phase (Φ<sub>DD</sub>) • Dynamic range: -180 to 180 deg • Resolution : 0.1 deg Accuracy:\$22deg@SNR&gt;10dB;r&lt;100Km;Δr&lt;1Km (1) Correlation Coefficient at zero lag (ρ<sub>NV</sub>) • Dynamic range : 0 to 1 • Resolution : 0.205 Accuracy:\$0.05@SNR&gt;10dB;r&lt;100Km;</pre>

#### 17564/2021/UAID DGMHQ

185/203	3
---------	---

		Δr<1Km	
2.37		<ol> <li>Provision shall be made for programmable and auto run mode of internal calibration to ensure reliability of polarimetric parameters.</li> </ol>	
	Calibration	II. Calibration through external equipment and validation of receiver linearity and dynamic range using standard coherent source and standard measuring equipment. There should be a provision for automatic update of radar parameters.	
		a) Receiver single point calibration in long and short pulse mode	
		b) System noise figure	
2.38	Sun calibration	and manual mode operation for pointing accuracy measurements. The system shall be made to point towards sum for establishing the gain and pointing accuracy of the antenna; stability and reliability of receiver chain using solar flux (sun) values known from other sources. Procedure shall be provided and to be demonstrated during SAT. Script based execution of such measurements and saving of results are expected as a part of such provision.	
2.39	Base Parameters to be measured	<pre>i. Reflectivity (2), j. Radial velocity (V), k. Spectrum Width (o), l. Differential reflectivity(Z<sub>200</sub>), m. Specific differential phase (K<sub>200</sub>), n_ Oifferential phase (Φ<sub>200</sub>), o, Cross correlation Coefficient (p<sub>200</sub>)</pre>	

## DGM-HQ-24014(11)/1/2021-UAID

2.40	Peripherals	<ul> <li>a) two merastrations intern &amp; Standby/ Of latest computer configuration at the time of delivery in terms of mother board chipset. Processor, processor speed, 128 SB RAM size and speed. Ethernet speed/USS speed, HDMI/VGA/DVI card memory and 4 TB hard disk storage with 32" (inches) full HD resolution, color LES monitor: Both Workstations shall be used for operation, control of the radars product generation and display of the data and shall have Raid Storage of the data to avoid any loss of data.</li> <li>b) Two workstations of latest configuration at the time of delivery in terms of mother bhard chipset, Processor, processor speed, 128 GB RAM size and speed. Ethernet speed/USB speed, MCMI/VGA/DVI card memory and hard disk storage processor with 32" (inches) full hD resolution, color LED monitor. Both Norkstations shall be used for networking/computer (laptop) of latest version/ configuration capeble of handling functions 6f a) &amp; h; above.</li> <li>c) One portable computer (laptop) of latest version/ configuration capeble of nandling functions 6f a) &amp; h; above.</li> <li>f) NAS storage with RAID with anchival for 05 years of base products as in 2.39.</li> <li>g) Provision for recording and playback of offline 16Q data.</li> <li>h) Provision for recording and playback of offline 16Q data.</li> <li>h) Provision for recording and playback of offline land operations.</li> <li>i) All software licenses shall be multiuser and oper, within radar group without any</li> </ul>
------	-------------	---

86

		restriction/hardware lock / soft- lock.
2.41	Power	(F). Power Requirements Capable of operating at 226±10% V, 50 ±2%Rs, in Single phase or400 ±10% V,
2.42	Online UPS	Two UPSs, in redundant mode and each capacity of at least 10 RVA, on line type, to run the whole radar system for et least 60 minutes. Catering to required voltage stabilization with a power factor suitable for the radar system.
2.43	Diesel Generator	At least 15 KVA suitable Diesel Generator Set with AMF panel for automatic turn ON when mains fails and capable to takes up the load (of all the essential components and accessories of the Radar system required for operation). The DG set should be silent with a separate canopy for operations in all weather conditions.

2.44	Pre- fabricated cabin.	A well-formished cabin of at least area 900 sq. feet is required to meet all operational requirements which includes operational room, Radar Officer room, UPS, stores, Kitchenette, microwave oven, Rest room/Washroom, along with ACs, water cooler, RO, furniture and separate outside canopy housing for D.G. set etc. to make it convenient for operational staff to work round the clock. The number of floors and dimensions of cabin may wary in size from site to site.	
		3. ARCHIVAL OF RADAR DATA	
a)	The base dat Spectrum Wid radar proces hard disk. N adequate cap for archival	a which includes Reflectivity, Velocity, th and Dual Pol. Parameters (output of sor) shall be stored automatically on atwork Attached Storage on SAID 5 with scity based on SATA disk, to be provided of Base Parameters data.	
ь)	A-4 size hi (600dpi pr h and products	<pre>gh resolution Ink tank Color Printer lgher) for taking hard copies of images shall be provided.</pre>	
с)	External Blu layer Blue ro at each site	e ray DVD writer with 12 disks of dual ry DVD R/W and 50 disks of Blue Ray DVD/R to be provided.	
৫)	Provision to analysis of 1	record, store and offline playback for 15 C data.	
		4. DATA FORMATS	
		4.1 Digital Data	
æ)	System should & Q) and g Radar Base d HDF5, XML, KM	i be capable of archiving of raw data (I enerating Polarimetric Doppler Weather ata and products in SUFR, NETCOF, GRIB2, 42 formate and NEXRAD-Level II formats.	
b)	Data should RAINFALL ACC selected leve	be converted from RAW, RAINFALL mm/hr, IMULATED in mm, Horizontal winds at user els in height, to Cartesian coordinates,	

Such data should also be available in HDFS, NetCDF, c) Stand-alone BUFR, NETCDF, HDFS, GRIB2, NexRAD-Level il encoding and decoding software on Licensed

	Linux/MS-WINDOWS platform should be provided. The software should be able to convert the radar data to formats as per user requirements and IMD	
d)	NetCDF format data shall be provided in NCAR CFRadial, and IMD-NetCDF format. Details of IMD- NetCDF format and SOFR-OPERA format file as required by IMD shall be provided to contractor for developing software applications.	
e)	Existing central server system at IMD HQ, New Welhi is based on Valsala (SIGMET) IRIS software for centrally generating various products including mesale and various data formats from RAW datas data products. The contractor should provide necessary provision to ingest their radar data in a compatible format for use with already available central server at New Delhi.	
f)	Data format if proprietary should be disclosed with decoding software codes.	
g)	The contractor shall provide data format converter to convert Baw Data as well as products to ASCII.	
imag publ reso foll for each fi s	es in (JPEG, GIF, TIFF, PNG) format files for ishing on web site. Images should have high lution for full 30 displays and also for web pages, awing file naming conventions are to be implemented automatic generation of images after completion of volume scan. ) cat_stn.gif Max 2 100km range ) ppz_stn.gif PFI 2 100km ) ppi_stn.gif PFI 2 100km ) ppi_stn.gif PFI 2 100km	
1 1 1	yp2_stn.gif VVP 43km Range/ up to 10 km height ) pr1_stn.gif SRI 100 km ) pa4_stn.gif PAC 100km accumulated rain for 24brs	
	5. SOFTWARE FEATURES	
e r Étwa	adar system should be having required menu driven me with DDI controls for:	
Sime	rating the radar.	

[D] 89

## DGM-HQ-24014(11)/1/2021-UAID

	av wy o and rotatimetric products sites applying	90
B)	The system shall generate base data comprising for Z. V. m and Polarimetric products after applying	
al	Un-filtered T & Q data archival and playback facility to generate base products.	
(2011)	5.1 Base Products	
produ proce liste	cts from the base data output from the radar signal ssor. Algorithms and references for all the products d below and supplied should be provided.	
The	System shall be capable of generating the following	
g) Th re re su	e system shall perform optimized correction of flectivity data for attenuation effects from heavy in based on algorithm using polarimetric parameters chas ZDR, $\phi_{DP}$ , $K_{DP}$ and $p_{BP}$ .	
p) Re	quisite software protection for denying unsuthorized cess to be provided.	
a) Si pk	multaneous display of data having more than one rameter.	
n) Fa dà	cility to reprocess and display products from past ta.	
m) Au us	tomatic transmission of warnings (visual and text) to ers via communication channels.	
1) 64 de	neration of audio-visual warnings based on user fined thresholds for severe weather detection.	
R) P2	odust display.	
)) Pr	oduct generation.	
(1) (1) (5) (5)	e process of setup/change of various scan parameters ould be easily accessible to operators using GUL.	
h) Mo	nitoring the health of the radar using BITS.	
g) Au ra	tomatic calibration for antenna, receivar, dynamic nge, etc.	
f) Se bo bo	tap of display overlaid on map of India with political undaries of international borders, states and district undaries.	
E) 56	tup of commanderion changels:	
由。	neration of alerts and warning,	
C) (60	nfiguration of weather products.	
Sec. 10.525		

1

	effect due to precipitation, earth curvature, range normalization, beam blockage, interference due to external sources; non-meteorological echoes, second- trip recovery, ground reflection, bright band correction, etc.)	
6)	Products are to be generated based on user defined parameters already selected and stored in workstation and NAS against the various scan schedules.	
đj	Provision also should be available to generate all products in offline mode using the archived raw data.	
	5.2 Primary Products	
ľhe bas and def sin cov	System shall compute and display maximum values of e data products (Z, V and d) in horizontal (East West North South) and vertical columns between users ined heights and also display the partial images in a gle frame with side panel heights to a scale of 2km ering 0 ~18 km.	
		_
S.2 The pro ele sch	.2 PPI (Plan Position Indicator) (Z,V,G) system should be capable of generating the PRI duct for all types of raw data at user selectable vation angles from lowest to highest elevation in the eduled scanning procedure.	
S.2 The pro ele sch S.2	.2 PPI (Plan Position Indicator) (2,V,G) system should be capable of generating the PBI duct for all types of raw data at user selectable vation angles from lowest to highest elevation in the eduled scanning procedure. .3 CAPPI (Constant Altitude Plan Position Indicator)	
S.2 The sro set <b>S.2</b> The set nei dat	2 PPI (Plan Position Indicator) (2,V,σ) system should be capable of generating the PBI duct for all types of raw data at user selectable vation angles from lowest to highest elevation in the eduled scanning procedure. 3 CAPPI (Constant Altitude Plan Position Indicator) System shall interpolate from the volume scan data for a geo-horizontal plane at user vertical defined ght and display the same pertaining to user selectable a form 2, V and σ from 1 km to 18 km height.	
S.2 The pro ele sch S.2 The set nei dat S.2	2 PPI (Plan Position Indicator) (2,V,G) system should be capable of generating the PRI duct for all types of raw data at user selectable vation angles from lowest to highest elevation in the eduled scanning procedure. 3 CAPPI (Constant Altitude Plan Position Indicator) System shall interpolate from the volume scan data for a geo-horizontal plane at user vertical defined ght and display the same pertaining to user selectable a form 2, V and G from 1 km to 18 km height. 4 PCAPPI (PSEUDO CAPPI)	
S.2 The sch S.2 The set dat S.2 The set sta beau and V a	.2 PFI (Plan Position Indicator) (2,V,G) system should be capable of generating the PSI duct for all types of raw data at user selectable vation angles from lowest to highest elevation in the eduled Scanning procedure3 CAPPI (Constant Altitude Plan Position Indicator) System shall interpolate from the volume scan data for a geo-horizontal plane at user vertical defined ght and display the same pertaining to user selectable a form 2, V and G from 1 km to 19 km height4 PCAPPI (PSEUDO CAPPI) system shall incorporate data form the highest vation scan near the radar and from lowest elevation n for areas far away from the radar for which radar ms are not intersected by user defined plane for CAPPI display same pertaining to data selected by user (2, nd G) from 1 km to 16 km height.	
S.2 The sch S.2 The set dat S.2 The set and V a S.2	.2 PPI (Plan Position Indicator) (2,V,G) system should be capable of generating the PPI duct for all types of raw data at user selectable vation angles from lowest to highest elevation in the eduled scanning procedure. .3 CAPPI (Constant Altitude Plan Position Indicator) System shall interpolate from the volume scan data for a geo-horizontal plane at user vertical defined ght and display the same pertaining to user selectable a form 2, V and o from 1 km to 18 km height. .4 PCAPPI (PSEUDO CAPPI) system shall incorporate data form the highest vation scan near the radar and from lowest elevation n for areas far away from the radar for which radar ms are not intersected by user defined plans for CSPPI display same pertaining to data selected by user (2, nd d) from 1 km to 18 km height. .5 VCUT (Vertical Cut)	

### 192/203

ter sin a difference a se	_
5.2.6 EBASE (ECHO BASE)	
The system shall identify from the volume scan data t minimum height up to which the user defined thresho value for each base data exists and display then for us selectable data.	he 13 er
5.2.7 ETOP (ECHO TOP)	-
The system shall identify from the volume scan data t maximum height up to which the user defined thresho value for each base data exists and display them for us selectable data.	he ld er
5.2.8 HAIL WARNING	-
Based on reliable hail warning algorithm, the syst shall generate a hail warning symbol at the appropria place in the PPI display in one or more of the operat chosen fields.	em ite or
5.2.9 HYDROMETEOR CLASSIFICATION	-
classification of hydrometeors based on Polarimetr	10
parameters $(E_{0k}, \Phi_{0k}, E_{0k})$ , $E_{0k}$ and $\rho_{(k)}$ . Provision for change parameters in a scientific way for sustainstation of t hydrometeor classification is a required. Hail detects based on this classification shall be one of the produc in this class.	the lon lon
parameters (E <sub>00</sub> , Φ <sub>00</sub> , S <sub>07</sub> and ρ <sub>00</sub> ). Provision for change parameters in a scientific way for customization of t hydrometeor classification is a required. Hail detection based on this classification shall be one of the product in this class. 5.3 Derived Meteorological Products:	ibe ion its
parameters (E <sub>00</sub> , Φ <sub>00</sub> , K <sub>07</sub> and ρ <sub>00</sub> ). Provision for change parameters in a scientific way for sustemization of t hydrometeor classification is a required. Bail detection based on this classification shall be one of the product in this class. 5.3 Derived Meteorological Products: 5.3.1 Velocity Products	be on ts
parameters (E <sub>00</sub> , Φ <sub>00</sub> , K <sub>07</sub> and ρ <sub>00</sub> ). Provision for change parameters in a scientific way for sustemization of t hydrometeor classification is a required. Bail detection based on this classification shall be one of the product in this class. 5.3 Derived Meteorological Products: 5.3.1 Velocity Products The system shall generate and display following velocion products:	ty
<pre>parameters (2<sub>00</sub>, 9<sub>00</sub>, 8<sub>07</sub> and p<sub>00</sub>). Provision for change parameters in a scientific way for customization of t hydrometeor classification is a required. Hail detects based on this classification shall be one of the product in this class. 5.3 Derived Meteorological Products: 5.3.1 Velocity Products The system shall generate and display following veloci products: ( Radial velocity versus the azimuth for a fixed elevati and a fixed slant range (VAD).</pre>	ty
<pre>parameters (E<sub>00</sub>, 0<sub>10</sub>, 8<sub>10</sub>, 8<sub>10</sub>, and 0<sub>10</sub>). Provision for change parameters in a scientific way for customization of t hydrometeor classification is a required, Hail detect based on this classification shall be one of the product in this class. 5.3 Derived Meteorological Products: 5.3.1 Velocity Products The system shall generate and display following veloci products: ( Radial velocity versus the azimuth for a fixed elevati and a fixed slant range (VAC). ( Radial velocity at a fixed user defined range on heid and azimuth angles (Radial velocity display for fix range, azimuth angles for versus height and azimuth).</pre>	te ch its its ity int ied
<pre>parameters (500, 900, 800 and 000). Provision for change parameters in a scientific way for customization of t hydrometeor classification is a required. Hail detects based on this classification shall be one of the product in this class. 5.3 Derived Meteorological Products: 5.3.1 Velocity Products The system shall generate and display following veloc) products: ( Radial velocity versus the azimuth for a fixed elevati and a fixed slant range (VAC). ( Radial velocity at a fixed user defined range on heic and a fixed slant range (VAC). ( Radial velocity at a fixed user defined range on heic and azimuth angles (Radial velocity display for fix range, azimuth angles for various height and azimuth). ( Horizontal wind velocity and wind direction using para in a vertical column above the radar site for differe heights including divergence &amp; converger product.(VVP_1)</pre>	ty its its its its its its its its



## 17564/2021/UAID DGMHQ

sarbs showing wind speed and direction in the time series manner for a user selectable time duration (VVP_2)	
a) Horizontal wind vectors (CWP) using barbs at user defined layer height with or without underlay of reflectivity or velocity in PPI / CAPPI format;	
5.3.2 Bydrological Products:	
The system shall generate and display following hydrological products:	
() Rainfall intensity using polarimetric moments as well as (-R in a user selectable surface layer and constants with constant height above ground. Provision of specifying freezing layer height dynamically.	
B) Instantaneous estimation of water content (VIL) residing in a user defined atmosphere layer in the atmosphere to be Hisplayed in PPI type of display.	
C) Precipitation accumulation (PAC) using polarimetric and D-R in a user definable time period.	
<ol> <li>Rainfall amount in user defined catchment basins for user lefined time span.</li> </ol>	
<ol> <li>Provision for putting river basin map overlay as per user requirement.</li> </ol>	
P) Rainfall intensity, rainfall rate and accumulation products shall have an option to be adjusted in real time by Rain Gauge, disdrometer data. Rain gauge and disdrometer ists shall be displayed along with the radar data.	
<ol> <li>Adjustment of rainfall rate by appropriate rain gauge or Hisdrometer data shall be possible.</li> </ol>	
i) The system shall convert data of reflectivity and oblarimetric measurement to horizontal maps of rainfall intensity.	
I) The system shall be capable of generating precise rain rate information using combination of polarimetric parameters as well as Z(h)	
7) The system shall use algorithm based on polarimetric parameters for correcting rain rate estimation errors arising but of hail, non-meteorological echoes and attenuation.	

## DGM-HQ-24014(11)/1/2021-UAID

#### 5.3.3 Aviation Products

- a) The system shall evaluate derivatives of wind velocity in radial, azimuth, elevation, North South, East West directions and derive horizontal, vertical and three dimensional shears
- b) The system shall also be able to generate warning product on microburst, and wind shears beyond adaptable threshold levels.
- c) The system shall evaluate maximum turbulence within user defined atmospheric layer and display in top view.

## 5.3.4 Warning and Forecasting Products:-

A. System shall generate and display warning symbols for thunderstorm, hail storm, dust storm, meso-cyclone, convergence, divergence and gust fronts.

B. System shall be capable of evaluating speed and direction of movement of weather systems.

c. System shall also be capable of warning if any of the conditions defined by the user are reached or fulfilled on reflectivity, velocity, VIL, rainfall intensity, rainfall accumulation and wind shear.

D. System shall be able to detect tornado and gust fronts associated with storms and issue visual and text warning message.

#### 5.4 Alphanumeric Products

The system shall also be able to provide all the product data (i.e. base, primary and derived) in ASCII tabular form.

### 6. Built in Test Equipment (BITE).

A modern system making use of latest technology for continuous monitoring of the operational status of hardware and software functions and utilities of the radar system shall be supplied.

ā.)	BITE processor shall measure and process a number of real time analog and digital parameters in the radar system and generate and display the error message whenever their value falls outside the specified permissible range.
60	BITE processor shall continuously monitor input and

putput signals of every module/PCB for any deviation.

## DGM-HQ-24014(11)/1/2021-UAID

:(2	Audio alarm indication for occurrences of faults is to be provided.	
d)	Centralized monitoring of status of radars networked.	
Pr	ovision for Networking & Communication system for data tran to central location	sf
æ§	Provision shall be made with suitable communication hardware & software for real time transfer of digital rudar data and images generated in real time through networking to control and monitoring centre and central server at IMD RQ, New Delbi.	
k)	All networking components required at radar site as well as command and control centre shall be provided by contractor.	
¢)	Necessary interface shall be provided for sending radar data through GSM, VPN and internet.	
d.)	The control centre should be able to monitor and control the functions of the radar at all eight sites. Data from respective radars under each site will be utilized for real time display facility for nonitoring the health parameters as well as the weather data accuired by radars in operational mode.	
<u>e)</u>	The communication link will be provided by IMD, contractor shall specify the bandwidth requirement.	
đ)	Deliverables for control and command centre are to be provided as per Annexure-VI.	
g):	The radar data is to be converted in a compatible format for use with already available central server of the existing Doppler weather radar network of IMD based on IRIS (SIGMET) software of M/S Valsala.	
	Boundary of states will be provided by IMD as shape files. Data of all radars to be overlayed on GIS map with option to include underlay maps from Google, Open street map or ESRL, Arc EIS, etc. GIS server with Open street map to be provided. The Products which are to be overlayed are:	
	• Reflectivity	
	• Sainfall	
	<ul> <li>Warnings based on Rainfall, Velocity, Hydrometeor Classification.</li> </ul>	

	8. INSTALLATION				
4)	Contractor shall take into consideration that the system is required to be installed on site on a Galvanized Steel Tower with nominal height of 20 m upon which radar antenna and radome shall be installed. Towers should be able to take the dynamic load of the radar system and its accessories while in operation, (with due consideration for the gusty wind load) and shall be wrected by contractor.				
b)	Walk/inspection space of about a meter width all around the radome base with a safety railing of 1.5m height is recommended for servicing of Radome. The railings should not degrade the signals of the radar during regular operations.				
¢)	The entire responsibility of civil construction/site preparedness for installation of the radar and its peripherals shall be the responsibility of the contractor.				
d)	Pre requisite for both civil 4 electrical requirements for installation of radar be clearly mentioned separately, inclusive of suitable diagrams of antenns 4 radoms installations, along with the technical bid.				
₩Ĵ.	The required number of electrical earthing based on latest technology i.e. Chemical Gel earthing is required for various peripherals inclusive of radar, has to be provided by contractor.				
£));	Suitable Lightning Arresters for protecting the radar with reliable lightning protection system with deep chemical gel and copper plate based earth pit shall be carried out by the contractor.				
ġ)	Aviation warning indicator lamps shall be supplied and installed by the contractor on the top of the antenna/radome at appropriate height.				
b.]	All other requirements such as power and communication facility etc. will be arranged by IMD for enabling tower construction and installation/ commissioning of radars of each respective site.				
£1	IMD may not facilitate the accommodation and transportation arrangements for the personnel of the installation team of the contractor.				

	9. LOCATION	
	List of tentative sites for installation of Badars is attached vide at Annesure-VIII.	
	10. TESTING AND ACCEPTANCE	
¢Σ.	Contractor shall submit detailed test plans for Eactory Acceptance Testing (FAT) prior to shipment and Site Acceptance Test (SAT) after installation at site for system acceptance. The test plan shall require concurrence by the ISD.	
¥.	During FAT, cost of travel, per diem charges and charges for Boarding/lodging for IMD personnel (5 persons) will be borne by IMD, Government of India.	
a)	The objective of the tests shall be the verification of performance of the system as per the specifications and functional requirements as per TENDER DOCUMENT.	
1):	As per the mutually agreed test procedures, FAT shall be parried out at the GEM's premises prior to shipment. The equipment shall be shipped only after satisfactory conclusion of the pre-shipment acceptance testing (FAT).	
	As per the mutually agreed test procedures, acceptance test should be carried out at each radar site after installation. Contractor shall arrange for necessary test equipment.	
ε¥.	Any defects / deviations noticed during the site acceptance tests shall be rectified within a maximum period of one month from the completion of the tests. After such rectification, the tests shall be repeated to verify the rectification.	
g).	Within 30 days of installation of each system, contractor should secure acceptance of the radar and its peripherals as a whole system.	
	11. SYSTEM COMMISSIONING	
er ss ab	the satisfactory completion of the site acceptance , contractor shall demonstrate the reliabilities and ility of the system to be operated continuously and	

	12 WARRANTY:	
a)	Warranty shall remain valid for three years after the system has been commissioned and accepted by IMD as per terms of the contract. The warranty shall also include all third party bought out items / subsystems including Tower, Computers, Generator Set and UPS; etc. GEM certification of warranty for the third party items is to be provided.	
ь)	This warranty clause is applicable at all individual radar sites.	
c)	Upon receipt of notice about faults, contractor shall repair or replace the defective goods or parts thereof, free of cost, at the site.	
d)	Contractor shall take over the replaced parts/ goods after providing their replacements and no claim, whatsdever shall lie on IMD for such replaced parts/ goods thereafter.	
e)	The contractor shall supply the software updates, if any, during the warranty and CAMC period, free of cost.	
£)	Supplier shall ensure 954 of 365 days annual-uptime.	
g)	If contractor, could not meet the 95% annual-uptime (calculated Quarterly at the time of payments) and there is a failure of the system for more than the criteria stipulated then a penalty amount of 0.5% of the total equipment cost per seven days for that radar, for days it is down, will be deducted from the performance guarantee amount, subject to an upper ceiling of 10% of the total equipment cost during warranty period and 10% of the total AMC cost during the AMC period. Furthermore IMD may proceed to take such remedial action(s) as deemed fit by IMD, at the risk and expense of contractor and without prejudice to other contractual rights and remedies, which IMD may have against contractor.	
h)	Maximum two weeks shutdown for Annual maintenance shall not come under the clause. Delay due to external factors and natural calamity beyond human control will be exempted.	

£)	During warranty period, contractor is required to visit consignee's site at least once is three months commencing from the date of acceptance at site for preventive maintenance, calibration and various types of checks of the goods/ equipment and a detailed report consisting of all test procedure values etc. must be submitted at Upper Air Instrument Division (UAID), India Meteorological Department, New Delhi along with satisfactory certification by the UAID (IMD).	
	13. TRAINING	
a)	Contractor shall provide factory training in operation, maintenance, calibration and fault identification of the radar system along with modification & up-gradation in application software to 4 persons from IMD at the factory premises for a period of 3 weeks.	
(đ	During factory training, cost of travel, per diem charges and charges for boarding/lodging for IMD personnel will be borne by IMD, Government of India.	
c)	The training shall also include lectures on the system design, computer herdware/software, operation and such other aspects which are considered essential for optimum utilization of the radar system.	
d)	Onsite training in operations and first level fault identification to be provided for a period of five working days.	
-	14. DOCUMENTATION:	
a)	Contractor shall furnish two copies of the following documentation in well-bound sets/volumes of good print quality for each radar site and two copies of the same to Radar Unit, UAID, New Deihi.	
b)	Soft copy of all the manuals should also be provided along with hard copy.	
c)	All standard manuals, technical data sheets and other pertinent information of functional, electrical and mechanical modules used in the System shall be included in the manuals.	
đ)	Interface connectivity document has to be provided for hardware as well as software interfaces.	
0)	Detailed documentation of all the proprietary data formats, bit-by-bit information on the header and data patterns should be provided.	

a

Free updates made to processing software and clarifications should also be supplied with relevant documentation during the period of warranty and CAMC thereof.	
The system functional block diagram shall be laid out so that a user can readily understand and identify the major functions of the system.	
The operating instructions shall include routine procedures, safety and energency procedures as applicable. These instructions shall include switch- on, standby, normal operating procedures and switch off procedures. The sequence of turn-on procedures shall be optimized for remote switching ON/OFF. The instructions shall provide assistance to an operator to use the System for optimum performance.	
Sufficient illustrations shall be included to identify and locate all operating controls and indicating devices.	
Layout and Schematic Assembly Drawings: Schematic Diagrams of all assemblies, modules shall be provided.	
Parts List: Detailed parts list with part numbers shall be provided.	
Algorithm of Products: The algorithms used in product generation shall be supplied.	
It shall be the responsibility of contractor to provide detailed parts list of modules sourced, bist of items imported and incorporated in the system should also be provided separately. Only such items may be used in the system whose technical details are made available by the manufacturer	
15. DELIVERY SCHEDULE	
First radar to be installed accepted and commissioned within 12 months from the date of issue of supply order. Rest of the radar systems shall be delivered, installed and commissioned within 33 months from the date of issue of supply order in a phased manner. In this regard the contractor will submit the actual schedule along with time line for execution of installation and commissioning work for each radar.	
	Free updates made to processing software and clarifications should also be supplied with relevant documentation during the period of warranty and CANC thereof. The system functional block diagram shall be leid out po that a user can readily understand and identify the major functions of the system. The operating instructions shall include routine procedures, wafety and emergency procedures as applicable. These instructions shall include soutch- on, standby, normal operating procedures and switch off procedures. The sequence of turn-on procedures shall be optimized for centre switching OM/OFF. The instructions shall provide assistants to an operator to use the System for optimum performance. Sufficient illustrations shall be included to identify and locate all operating controls and indicating devices. Layout and Schematic Assembly Drawings: Schematic Diagrams of all assemblies, modules shall be provided. Parts List: Detailed parts list with part numbers shall be provided. Algorithm of Products: The algorithms used is product generation shall be supplied. It shall be the responsibility of contractor to provide detailed parts list of modules sourced, bist of items imported and incorporated in the system about also be provide separately. Only such items may be used in the system whose technical details are made available by the manufacturer <b>15. DELIVERY SCHEDULE</b> First radar to be installed accepted and commissioned within 12 months from the date of issue of supply primer. Best of the radar system shall be delivered, installed and commissioned within 33 months from the date of issue of supply order in a phased manner. In this regard the contractor will submit the actual schedule along with time line for execution of installed and commissioned within 13 months from the date of issue of supply order in a phased manner. In this regard the contractor will submit use actual

b) c)	11.Installation of all equipment to test the first radar within one month after supply of all stores. 11. Acceptance and commission of first Radar within one month after installation. 1v.Supply, installation, acceptance and commissioning of seven remaining radars will be executed in every three months, within a total period of 33 months, from the issue of supply order. Preliminary Design Review (FDR) will be held after one month from the date of issue of supply order where in the design of hardware & software to be delivered as part of the system will be discussed at the office of UAID, IMD, New Onlbi (India). Critical Design Review (COR) will be conducted within six months from the date of issue of supply order	
b) c)	<ul> <li>iii. Acceptance and commission of first Radar within one month after installation.</li> <li>iv.Supply, installation, acceptance and commissioning of seven remaining radars will be executed in every three months, within a total period of 33 months, from the issue of supply order.</li> <li>Preliminary Design Review (FDR) will be held after one month from the date of issue of supply order where in the design of hardware &amp; software to be delivered as part of the system will be discussed at the office of UAID, IMD, New Onlhi (India).</li> <li>Critical Design Review (CDR) will be conducted within six months from the date of issue of supply order where in the design along with performance parameters</li> </ul>	
(d (2	iv.Supply, installation, acceptance and commissioning of seven remaining radars will be executed in every three months, within a total period of 33 months, from the issue of supply order.           Preliminary Design Review         (FOR) will be held after one month from the date of issue of supply order where in the design of hardware & software to be delivered as part of the system will be discussed at the office of UAID, IMD, New Delhi (India).           Critical Design Review         (COR) will be conducted within six months from the date of issue of supply order	
b) c)	Preliminary Design Review (FDR) will be held after one month from the date of issue of supply order where in the design of hardware & software to be delivered as part of the system will be discussed at the office of UAID, IMD, New Delhi (India). Critical Design Review (CDR) will be conducted within six months from the date of issue of supply order where in the design along with performance parameters	
c)	Critical Design Review (COR) will be conducted within six months from the date of issue of supply order where in the design along with performance parameters	
	of the sub units will be discussed in details to ensure that the system achieves the performance parameters to be delivered as per TENGER DOCUMENT.	
16	.Penalty clause/Liquidated damages clause (LD) for delayed stores & Services:	
he LJ er C Mectin	D will be imposed if delivery schedule is not met as hapter 2 in Clause No. 20 and Clause No. 15 of this on.	
17	. COMPREHENSIVE ANNUAL MAINTENANCE CONTRACT (CAMC)	
a)	The Bidder shall quote for CAMC for seven years which will commende subsequent to successful completion of warranty period of three years.	
b)	The Bidder shall submit the year wise lump sum amount of CAMC charges for each radar/site.	
c)	The amount charged for CAMC shall not be quoted as percentage of the tender cost / cost of equipment.	
d)	The CAMC charges shall be included for price comparison. The terms & conditions for the CAMC are enclosed at Annexure-V.	

Ok\_

41

202/203

Annexure XIII

## Format for Affidavit of Self Certification regarding Local Content in a Doppler Weather Radar

Dates

S/0, D/0, W/0 , Resident of

do hereby solemnly

affirm and declare as under:

That I will agree to abide by the terms and conditions of the policy of Government of India issued vide Notification - Public Procurement (preference to make in India) Order 2017 dated 15<sup>th</sup> June , 2017 and subsequently 04<sup>th</sup> June 2020 and 16<sup>th</sup> September, 2020.

That the information furnished hereinafter is correct to be of my knowledge and belief and I undertake to produce relevant records before the procuring entity or any authority so nominated for the purpose of assessing the local content.

That the local content for all inputs which constitute the said equipment has been verified by me and I an responsible for the correctness of the claims made therein.

That in the event of domestic value addition of the product mentioned herein is found to be incorrect and not meeting the prescribed value addition norms, based on the assessment of an authority so nominated for the purpose of assessing the local content, action will be taken against me as per Order No. P-45021/2/2017/-E.E.-TI dated 15.06.2017.

I agree to maintain the following information in the Company's record for a period of 03 years and shall make this available

102

#### 17564/2021/UAID DGMHQ

for verification to any statutory wotherity: (Kindly fill up the below mentioned particulars)

- 1.Name and details of the Domestic Manufacturer (Registered Office, Manufacturing Unit location, nature of legal entity)
- if. Date on which this cortificate is issued
- iii.Doppler weather radar for which the certificate is produced
- Iv.Produring entity to whom the mertificate is furnished v.Percentage of local content claimed
- vi.Name and contact details of the unit of the manufacturer
- vii. Sale Price of the Product
- viil.Ex-Factory Price of the product
  - ix. Freight, insurance and handling
  - x.Total bill of Material
  - xi.List and total cost value of inputs used for manufacture of the Doppler weather radar
  - xii.List and total cost of inputs which are imported, directly or indirectly

## For and on behalf of

## (Name of firm/entity)

Authorized signatory

(To be duly signed by the Board of Director)